

DAFTAR SINGKATAN

AMD	: <i>Software Defined Network</i>
API	: <i>Application Program Interface</i>
ARP	: <i>Address Resolution Protocol</i>
BGP	: <i>Border Gateway Protocol</i>
CLI	: <i>Command Line Interface</i>
CPU	: <i>Central Processing Unit</i>
D-ITG	: <i>Distributed Internet Traffic Generator</i>
DV	: <i>Distance Vector</i>
EGP	: <i>Exterior Gateway Protocol</i>
EIGRP	: <i>Enhanced Interior Gateway Routing Protocol</i>
FIB	: <i>Forwarding Information Base</i>
HD	: <i>High Definition</i>
ICMP	: <i>Internet Control Message Protocol</i>
IGP	: <i>Interior Gateway Protocol</i>
IGRP	: <i>Interior Gateway Routing Protocol</i>
IS-IS	: <i>Intermediate System to Intermediate System</i>
ITU-T	: <i>International Telecommunication Union Telecommunication Standardization Sector</i>
LS	: <i>Link State</i>
LXC	: <i>Linux Container</i>
NetID	: <i>Network Identity</i>
OSPF	: <i>Open Shortest Path First</i>
OWD	: <i>One-Way Delay</i>
PLR	: <i>Packet Loss Ratio</i>
QoS	: <i>Quality of Service</i>
RAM	: <i>Random Access Memory</i>
RFC	: <i>Request for Comments</i>
RFClient	: <i>RouteFlow Client</i>
RFProxy	: <i>RouteFlow Proxy</i>
RFServer	: <i>RouteFlow Server</i>

RIP	: <i>Routing Information Protocol</i>
RIPv2	: <i>Routing Information Protocol version 2</i>
RTO	: <i>Request Time Out</i>
SDN	: <i>Software Defined Network</i>
TCP	: <i>Transmission Control Protocol</i>
UDP	: <i>User Datagram Protocol</i>
UTP	: <i>Unshielded Twisted Pair</i>
VAD	: <i>Voice Activity Detection</i>
VGA	: <i>Video Graphics Array</i>
VM	: <i>Virtual Machine</i>
VoIP	: <i>Voice over IP</i>