

TABLE OF FIGURES

Fig. 1.1	Gap between existing condition with the simulation	2
Fig. 2.1	The evolution of cellular network	5
Fig. 2.2	Bandwith capacity for various cellular network	6
Fig. 2.3	Voip network	8
Fig. 2.4	VOIP subscriber growth for Mobile VOIP	8
Fig. 2.5	Network QoS & End to End QoS	9
Fig. 2.6	Factor Affect Voice Quality in VOIP	9
Fig. 2.7	IMS Access Network	10
Fig. 2.8	IMS Call Flow – Initiation Multimedia Session	13
Fig. 2.9	Graphic previous simulation result	15
Fig. 2.10	Call Setup Delay for VOIP in IPv4 and IPv6 on IMS Network	16
Fig. 3.1	Flowchart of simulation	17
Fig. 3.2	The topology of IMS network simulation	18
Fig. 3.3	Topology Of Cellular Network Interworking With IMS	19
Fig. 3.4	Clock Synchronization	19
Fig. 3.5	SIP Transactions	21
Fig. 3.6	SIP Register Session	21
Fig. 3.7	Establishment of Call Setup Delay Process	22
Fig. 3.8	Voice call simulation	23
Fig. 3.9	Video Call Simulation	24
Fig. 3.10	Details of MSRP message	25
Fig. 3.11	Chat message session	26
Fig. 3.12	Distance between IMS client and base station	27
Fig. 3.13	Top highest traffic operator in Indonesia	28
Fig. 3.14	Movial Communicator	29
Fig. 3.15	Wireshark	30
Fig. 4.1	Comparison of call setup delay	32
Fig. 4.2	Aggregate comparison of call setup delay	32
Fig 4.3	SIP Register	33
Fig. 4.4	End to end delay comparison	34
Fig. 4.5	Aggregate comparison of end to end delay	34
Fig. 4.6	Jitter comparison	35
Fig. 4.7	Throughput comparison	35
Fig. 4.8	Throughput of voice call	36
Fig. 4.9	Throughput of video call	36
Fig. 4.10	Throughput of instan messaging	37
Fig. 4.11	Call setup delay to E2E delay comparison	37
Fig. 4.12	Bandwidth to E2E delay comparison	38