

## List of Tables

2.1	NG-PON2 splitting ratio options . . . . .	9
2.2	Wavelength bands defined by IT for NG-PON2 based in WDM . . . . .	12
2.3	WDM-PON Downstream and Upstream Channel Grid Examples . . . . .	12
2.4	Typical Properties Of Some Commercially Available Transmission fibres at 1550 nm [1] . . . . .	21
2.5	Transmission Distances Of An NRZ Signal For 1-dB Eye-Closure Penalty Due To Dispersion [1] . . . . .	21
3.1	Device and component parameters . . . . .	24
3.2	Attenuation fibre coefficient $\alpha$ in deployment environment . . . . .	27
3.3	Reflectance and insertion losses due to splices, & connectors . . . . .	28
3.4	Reference values of wavelength . . . . .	28
3.5	Reference values for dispersion coefficient and dispersion slope . . . . .	28
3.6	Typical values for Uniformity parameter for Power splitters . . . . .	29
3.7	PDL values for power splitter . . . . .	29
3.8	Insertion losses for power splitter . . . . .	30
3.9	Typical values of Optical tunable filters . . . . .	30
4.1	Comparison of Power Receive . . . . .	41
4.2	Comparison of Q-Factor . . . . .	41
4.3	Proposed operating parameters for a thermal AWG model . . . . .	43
4.4	Power to temperature changes . . . . .	45