ABSTRACT

The problem of queue is how to balance the waiting costs and preventing cost of the queue to gain maximum profit. Queuing analysis can be done by knowing arrival distribution, service time distribution, queue discipline and queuing model. The purpose of the paper are to calculate the optimal number of servers so users do not wait too long in line, know the queue model in accordance with queuing conditions, and improve the efficiency and performance of servers.

The result of queuing system performance based on analysis and calculation shows that the queue model is (M/G/8): $(FIFO/\infty/\infty)$. The average time the customer waits in the queue is 17,17 minutes and the average service time per customer is 14.39 minutes. Customer is served for 14.39 minutes but before being served it must wait for 17.17 minutes. This condition indicates that waiting time is more than serving time. The system utility level at GraPARI Banda Aceh is 95.50%, it indicates that utility is so high that it should be repaired to optimize the utility. The waiting time in the queue is 17.17 minutes, the waiting time in the system is 31.66 minutes and the queue length in the system is 17 people. This will make the bottleneck of customers who will queue before being served. Based on the analysis of the new design, it is known that the addition of 1 server from 8 to 9 servers is the most optimal solution. The addition of 1 server can reduce the system utility up to 84.90% and waiting time in the queue is 2.91 minutes, waiting time in the system 17.4 minutes and the queue length in the system 2.91 minutes, also shows the solution can reduce the cost of queue.

Keywords: queuing system, queuing model, M/G/8, FIFO, service quality