

DAFTAR SINGKATAN

RSSI	= Received Signal Strength Indicator
RSRP	= Reference Signal Received Power
SINR	= Signal to Interference Noise Ratio
BLER	= Block Error Rate
MS	= Mobile station
LTE	= <i>Long Term Evolution</i>
BTS	= <i>Base Transceiver Station</i>
eNode B	= <i>Evolved Node B</i>
QoS	= <i>Quality Of Service</i>
BS	= <i>Base Station</i>
EPC	= <i>Evolved Packet Core</i>
RNS	= <i>Radio Network Controller</i>
RF	= <i>Radio Frequency</i>
DC	= <i>Power Supply</i>
CQI	= <i>Channel Quality Index</i>
RB	= <i>Resource Block</i>
ACP	= <i>Automatic Cell Planning</i>
OFDM	= <i>Orthogonal Frekuensi Division Multiplexing</i>
MAPL	= <i>Maximum Allowed Path Loss</i>
MIMO	= <i>Multiple input multiple output</i>
BHSA	= <i>Busy Hour Service Attempt</i>
QAM	= <i>Quadrature amplitude modulation</i>
PER	= <i>Packet Error Rate</i>
LOS	= <i>Line of sight</i>
KPI	= <i>Key Performance Indicator</i>
OFDMA	= <i>Orthogonal Frequency Division Multiple Access</i>
SC-OFDMA	= <u><i>Single Carrier Frequency Division Multiple Access</i></u>
IP	= <i>Internet Protocol</i>
PDCP	= <i>Packet Data Convergence Protocol.</i>
CRC	= <i>Cyclic Redundancy Check</i>
EARFCN	= <i>E-UTRA Absolute Frequency Channel Number</i>

MAC = *Media Access Control*

QPSK = *Quadrature Phase Shift Keying*

RSRP SC = *Reference Signal Received Power Serving Cell*

RSRP MN = *Reference Signal Received Power Neighbour*