

## List of Figures

1.1	The lateral view of the experiment with the parameters $H_0 = 0.20$ m, $H_S = 0.10$ m, $L_u = 3.00$ m, $L_d = 3.03$ m and $L_1 = 1.00$ m. The value of $\Phi$ are depend on $X_{TOP}$ and $X_{TOE}$ . . . . .	2
2.1	Sketch of 1D shallow water equations and their primitive variables.	4
2.2	1D <i>staggered grids</i> . The orange area represents volume control for mass conservation, association with unknown $h_i$ and $z_i$ . Volume control for momentum conservation ( $u_{i+\frac{1}{2}}$ ) shown in red area.	5
3.1	Flowchart algorithm of Dam-break over an erodible embankment Simulation. . . . .	7
4.1	The comparison of numerical result and data experiment dam-break over an erodible embankment [2]. Figures (a), (b) and (c) are the comparison results in slope $\Phi = 59.04$ using $A_g = 9 \times 10^{-6}$ , $A_g = 10^{-5}$ and $A_g = 2 \times 10^{-5}$ respectively. Figures (d), (e) and (f) are the comparison results in slope $\Phi = 41.42$ using $A_g = 9 \times 10^{-6}$ , $A_g = 10^{-5}$ and $A_g = 2 \times 10^{-5}$ respectively.	10