

## LIST OF FIGURES

2.1 Usage scenarios of IMT for 2020 and beyond (source:ITU-R) . . . . .	7
2.2 An illustration of the key design parameters for 5G mobile antennas. (source:IEEE microwave magazine) . . . . .	9
2.3 Vivaldi Configuration (a)top view (b)bottom view[3] . . . . .	10
2.4 Impedance Matching[4] . . . . .	11
2.5 Microstrip Feedline [4] . . . . .	12
2.6 Geometry of a two-element array positioned along the z-axis[4] . . . . .	13
2.7 Butler Matrix Component . . . . .	15
2.8 Symbol of 90° Hybrid Coupler[5] . . . . .	16
2.9 Geometry of 90° Hybrid Coupler[5] . . . . .	16
2.10 Illustration of Crossover function . . . . .	17
2.11 Geometry of 90° Crossover [5] . . . . .	17
2.12 Configuration of ideal phase shifter [5] . . . . .	18
3.1 Stages of the research flow . . . . .	20
3.2 Design of Butler Matrix and Vivaldi Array Antenna . . . . .	23
3.3 Flow chart of 4×4 Butler Matrix . . . . .	24
3.4 Geometry of Quadrature Hybrid . . . . .	25
3.5 Geometry of Hybrid 90° after optimization . . . . .	25
3.6 Insertion Loss, Return Loss and Isolation in Hybrid 90° . . . . .	26
3.7 Phase Difference in Port 3 and Port 4 . . . . .	26
3.8 Power flow of 90° Hybrid . . . . .	27
3.9 Geometry of Cross Over . . . . .	27
3.10 Geometry of Cross Over . . . . .	28
3.11 S-Parameter at 28 GHz for Cross Over . . . . .	28
3.12 Power flow of Cross Over . . . . .	29
3.13 Geometry of phase shifter . . . . .	29
3.14 Phase (S12) for -45° phase shifter at 28 GHz . . . . .	30
3.15 Phase (S12) for -45° phase shifter at 28 GHz . . . . .	30
3.16 Geometry of path connector . . . . .	30
3.17 S-Parameter at 28 GHz for path connector . . . . .	31
3.18 Flow chart of single and array antenna . . . . .	32
3.19 Vivaldi Dimension (a)top view (b)bottom view . . . . .	32
3.20 Return loss S11 single element after before optimization . . . . .	34
3.21 Single antenna after optimization(a)top view (b)bottom view . . . . .	34
3.22 Returnloss (S11) of vivaldi based on calculation . . . . .	35
3.23 VSWR of single element after optimization . . . . .	35
3.24 Gain of single element antenna . . . . .	36
3.25 Single element radiation pattern in azimuth . . . . .	36
3.26 Single element radiation pattern in elevation . . . . .	36
3.27 Simulation of array antenna in (a)top view (b)bottom view . . . . .	37

3.28	S-Parameter of 1×4 array antenna . . . . .	37
3.29	VSWR of 1×4 array antenna . . . . .	38
3.30	Gain of 1×4 array antenna . . . . .	38
3.31	Radiation Pattern 1×4 in elevation . . . . .	39
3.32	Radiation Pattern 1×4 in azimuth . . . . .	39
3.33	Design of mobile phone (a)top view (b)right view (c)left view(d)bottom view . . . . .	39
3.34	Design of mobile phone and antenna array (a)top view (b)bottom view .	40
4.1	Optimized 4×4 Butler Matrix . . . . .	42
4.2	Phase Simulation Result in Port 1 . . . . .	43
4.3	Phase Simulation Result in Port 2 . . . . .	43
4.4	Phase Simulation Result in Port 3 . . . . .	43
4.5	Phase Simulation Result in Port 4 . . . . .	44
4.6	Return loss and insertion loss in (a)port 1(b)port 2(c)port 3(d)port 4 . .	45
4.7	VSWR of butler matrix in (a)port 1(b)port 2(c)port 3(d)port 4 . . . . .	46
4.8	Final configuration of butler matrix and antenna (a)top view (b)bottom view . . . . .	47
4.9	Power Flow in (a)port 1(b)port 2(c)port 3(d)port 4 . . . . .	47
4.10	Radiation Pattern in Port 1 (phase difference of -45°) . . . . .	48
4.11	Radiation Pattern in Port 2 (phase difference of 135°) . . . . .	48
4.12	Radiation Pattern in Port 3 (phase difference of -135°) . . . . .	48
4.13	Radiation Pattern in Port 4 (phase difference of 45°) . . . . .	49
4.14	Radiation Pattern in all port . . . . .	49
4.15	Cartesian radiation patterns in (a)Port 1(b)Port 2 (c)Port 3(d)Port 4 .	50
4.16	Modeling of mobile phone using software (a)top side (b)bottom side . .	50
4.17	Mobile phone include sub array-butler matrix (a)top side (b)bottom side	51
4.18	Radiation pattern in all input . . . . .	52
4.19	Radiation pattern in left side (Port 1-4) . . . . .	52
4.20	Radiation pattern in top side (Port 5-8) . . . . .	53
4.21	Radiation pattern in right side (Port 9-12) . . . . .	53
4.22	Radiation pattern in all port . . . . .	53
4.23	Simulation in (a)free space (b)browsing mode (c)talking position (d)talking position with hand . . . . .	54