

DAFTAR ISI

| | |
|---|-----|
| HALAMAN JUDUL | i |
| LEMBAR PENGESAHAN | iii |
| ABSTRAK | iv |
| <i>ABSTRACT</i> | v |
| KATA PENGANTAR | vi |
| UCAPAN TERIMA KASIH | vii |
| DAFTAR ISI | ix |
| DAFTAR GAMBAR..... | xii |
| DAFTAR ISTILAH..... | xvi |
| BAB I PENDAHULUAN | 1 |
| 1.1 Latar Belakang | 1 |
| 1.2 Rumusan Masalah | 2 |
| 1.3 Tujuan Dan Manfaat | 2 |
| 1.4 Batasan Masalah | 3 |
| 1.5 Metodologi..... | 3 |
| 1.6 Sistematika Penulisan | 4 |
| BAB II DASAR TEORI..... | 5 |
| 2.1 Teknologi 4G Long Term Evolution (LTE) | 5 |
| 2.1.1 Arsitektur Jaringan <i>Long Term Evolution</i> (LTE)..... | 5 |
| 2.1.2 <i>Resource Block</i> (RB)..... | 7 |
| 2.2 <i>Indoor Building Coverage</i> | 9 |
| 2.2.1 Kondisi Propagasi | 9 |
| 2.2.2 Perencanaan Jaringan Indoor | 10 |
| 2.3 Sistem Antena <i>Indoor</i> | 11 |
| 2.4 <i>Capacity Planning</i> | 13 |
| 2.4.1 <i>Estimasi User</i> | 13 |
| 2.4.2 <i>Service And Traffic Model Parameter</i> | 14 |
| 2.4.3 <i>Peak To Average Ratio</i> | 14 |
| 2.4.4 <i>Single User Throughput</i> | 14 |
| 2.4.5 <i>Network Throughput</i> | 15 |
| 2.4.6 <i>Single Site Capacity</i> | 15 |

| | |
|---|----|
| 2.4.7 Jumlah Antena..... | 16 |
| 2.5 <i>Coverage Planning</i> | 16 |
| 2.7.1 Map Dan Luas Gedung | 17 |
| 2.5.1 Model Propagasi..... | 17 |
| 2.5.2 <i>Engineering Parameter</i> | 18 |
| 2.5.3 <i>Radius Antena</i> | 19 |
| 2.5.4 Luas Cakupan Antena | 20 |
| 2.5.5 Jumlah Antena..... | 20 |
| 2.6 Rf Parameter | 20 |
| 2.6.1 <i>Reference Signal Received Power (RSRP)</i> | 20 |
| 2.6.2 <i>Signal To Interference Plus Noise Ratio (SINR)</i> | 21 |
| 2.7 <i>Walk Test</i> | 21 |
| 2.8 TEMS Pocket..... | 21 |
| 2.9 Radiowave Propagation Simulation (RPS)..... | 21 |
| BAB III..... | 22 |
| PERANCANGAN SISTEM..... | 22 |
| 3.1 Deskripsi Proyek Akhir | 22 |
| 3.2 Perancangan <i>Indoor Building Coverage</i> | 22 |
| 3.3 Penentuan dan Survei Gedung | 23 |
| 3.3.1 Penentuan Daerah | 26 |
| 3.4 Desain <i>Layout</i> Gedung..... | 26 |
| 3.5 <i>Drive Test</i> | 27 |
| 3.6 Analisis dan <i>Reporting Hasil Drive Test</i> | 28 |
| 3.7 Analisis dan <i>Reporting Hasil Walk Test</i> | 29 |
| 3.8 <i>Capacity Planning</i> | 31 |
| 3.8.1 <i>Forecasting Number of User</i> | 31 |
| 3.8.2 <i>Service and Traffic Model Parameter</i> | 33 |
| 3.8.3 <i>Single User Throughput</i> | 34 |
| 3.8.4 <i>Network Throughput</i> | 35 |
| 3.8.5 <i>Single Site Capacity</i> | 35 |
| 3.9 <i>Coverage Planning</i> | 36 |
| 3.9.1 Persiapan <i>layout</i> dan Luas Gedung..... | 37 |
| 3.9.2 <i>Engineering Parameter</i> | 37 |

| | |
|---|----|
| 3.9.3 <i>Link Budget</i> | 39 |
| 3.9.4 Perhitungan Model Propagasi, <i>Path Loss</i> dan <i>Radius Antenna</i> | 41 |
| BAB IV KELUARAN DAN ANALISA..... | 44 |
| 4.1 Penentuan Letak Perangkat Aktif dan Pasif | 44 |
| 4.2 Penentuan Jumlah Antena..... | 44 |
| 4.3 <i>Wiring Diagram</i> | 45 |
| 4.4 <i>IBC Planning</i> Pada <i>Software RPS</i> | 45 |
| 4.5 Analisa dan Hasil Simulasi | 46 |
| 4.6 Perbandingan Hasil Perencanaan dengan <i>WT Initial</i> | 50 |
| BAB V | 52 |
| KESIMPULAN DAN SARAN | 52 |
| 5.1 Kesimpulan | 52 |
| 5.2 Saran | 52 |
| DAFTAR PUSTAKA..... | 54 |