

DAFTAR SINGKATAN

AMC	: <i>Adaptive Modulation and Coding</i>
BS	: <i>Base Station</i>
CINR	: <i>Carrier Interference Noise Ratio</i>
DAS	: <i>Distributed Antenna System</i>
EIRP	: <i>Effective Isotropic Radiated Power</i>
IBC	: <i>Indoor Building Coverage</i>
IP	: <i>Internet Protocol</i>
Kbps	: <i>Kilo bit per second</i>
KPI	: <i>Key Performance Indicator</i>
LTE	: <i>Long Term Evolution</i>
MAPL	: <i>Maximum Allowable Path Loss</i>
Mbps	: <i>Mega bit per second</i>
MCS	: <i>Modulation and Coding Scheme</i>
Mhz	: <i>Mega Hertz</i>
MIMO	: <i>Multiple Input Multiple Output</i>
NRB	: <i>Number of Resource Block</i>
PCI	: <i>Physical Cell Identity</i>
RF	: <i>Radio Frequency</i>
RPS	: <i>Radiowave Propagation Simulation</i>
RSL	: <i>Received Signal Level</i>
RSRP	: <i>Reference Signal Receive Power</i>
RSSI	: <i>Receive Signal Strength Indicator</i>
SINR	: <i>Signal Interference Noise Ratio</i>
SIR	: <i>Signal Interference Ratio</i>
SUT	: <i>Single User Throughput</i>
UE	: <i>User Equipment</i>
UL	: <i>Uplink</i>