ABSTRACT

Telkom University dorm is home to students who are kept safe, because there are important

valuables such as laptops, books, and pocket money. It is used by Universitas Telkom students to

support academic and non-akdemic skills. Therefore, it takes security to prevent something

unwanted, such as being entered by an irresponsible party. To prevent this, extra security is

required for the occupants of the room or visitors to enter the dormitory rooms. These safeguards

can be implemented by creating an integrated entrance with RFID (Radio frequency Identification)

that will be connected to the KTM student/I.

Currently, the entrance of the dormitory at Telkom University is still using manual

admission. Such as filling in the guest book, or filling the room occupants book. However, in the

process is not efficient against time and security, often there is a loss of goods or any entry party

irresponsible. Therefore RFID is used for dorm room door, and from the RFID can detect KTM.

Therefore, in this research, conducted the design and implementation of RFID-based doors on the

hostel Univeritas Telkom.

In research, authors use Arduino to manage the connected RFID Reader. By having a test

parameter that can show its performance. RFID Reader is able to read student sign cards of

dormitory room owners. Average distance 3.5 cm if without barrier. And if there is a barrier 2 cm.

To perform the distance between taping to the other tapping has an average delay of 2.72 seconds.

For the average time the reader used in < 1 second detection. For testing the tilt degree that can be

detected is a 10 ° angle with a maximum distance of 3.5 cm. angle 20 ° with a maximum distance

of 3 cm. Angle 30 ° with a maximum distance of 2.5 cm. Angle of 40 ° with a maximum distance

of 2 cm. So that it can be concluded that the appliance on This research can answer the problems

that occur.

Keywords: Radio Frequency Identification, Arduino, Dormitory

٧