

DAFTAR PUSTAKA

- [1] A. Rahman and M. Suryanegara, “The development of IoT LoRa: A performance evaluation on LoS and Non-LoS environment at 915 MHz ISM frequency,” *Proc. - Int. Conf. Signals Syst. ICSigSys 2017*, pp. 163–167, 2017.
- [2] E. D. Meutia, “Internet of Things – Keamanan dan Privasi,” *Semin. Nas. dan Expo Tek. Elektro 2015*, pp. 85–89, 2015.
- [3] Indria, Nolanda; Kurniawan and Teguh, “PERANCANGAN _JARINGAN NIRKABEL SEBAGAI REDUDANCY LINK PADA INFRASTRUKTUR WAN YAYASAN KESEHATAN (YAKES) TELKOM BANDUNG MENGGUNAKAN METODOLOGI NETWORK DEVELOPMENT LIFE CYCLE (NDLC) _____,” *e-Proceeding Eng.*, vol. 4, no. 3, p. 3065, 2017.
- [4] R. K. Kodali, “Radio data infrastructure for remote monitoring system using LoRa technology,” *2017 Int. Conf. Adv. Comput. Commun. Informatics, ICACCI 2017*, vol. 2017–Janua, pp. 467–472, 2017.
- [5] Orange, “LoRa Device Developer Guide,” p. 42, 2016.
- [6] T. Tri Saputro, “Mengenal Node MCU : Pertemuan Pertama,” 2017. [Online]. Available: <https://embeddednesia.com/v1/tutorial-nodemcu-pertemuan-pertama/>. [Accessed: 06-Nov-2018].
- [7] M. R. Hidayat, C. Christiono, and B. S. Sapudin, “PERANCANGAN SISTEM KEAMANAN RUMAH BERBASIS IoT DENGAN NodeMCU ESP8266 MENGGUNAKAN SENSOR PIR HC-SR501 DAN SENSOR SMOKE DETECTOR,” *Kilat*, vol. 7, no. 2, pp. 139–148, 2018.
- [8] A. Lavric and V. Popa, “Internet of Things and LoRa™ Low-Power Wide-Area Networks: A survey,” *ISSCS 2017 - Int. Symp. Signals, Circuits Syst.*, 2017.

- [9] S. Jumiati, "Analisa Bandwidth Menggunakan Metode Antrian," vol. 2, no. 2, pp. 244–257, 2017.
- [10] W. Stabb, "Intelligibility vs. Bandwidth," 2014. [Online]. Available: <https://hearinghealthmatters.org/waynesworld/2014/intelligibility-vs-bandwidth/>. [Accessed: 16-Jan-2019].
- [11] H. Factors, *Final draft ETSI EN 300 220-1 V2.4.1 (2012-01)*, vol. 0. 2014, pp. 1–73.
- [12] S. Rifka, F. Firdaus, and W. F. Ramadhan, "Penerapan Embedded System pada Sistem Pintar Pengendali Multi Perangkat dalam Kelas berbasis Intel Galileo dan Web," *J. Rekayasa Elektr.*, vol. 14, no. 1, pp. 51–61, 2018.
- [13] T. Nurpita Sari, Rini;Suwandi;Suryani, "Implementasi dan Evaluasi Kinerja Frequency Hopping Spread Spectrum (FHSS) Menggunakan WARP," *J. Tek. ITS*, vol. 4, no. 1, 2015.
- [14] E. Committee and R. Regulations, *Rec. ITU-R SM.329-7*, vol. 1, no. 139. 1997, pp. 1–23.
- [15] T. Laboratory, "Unwanted emissions of multi-carrier transmitter in spurious domain," 2015. [Online]. Available: http://tanaka-lab.ee.cit.nihon-u.ac.jp/E_Research_Spurious.html. [Accessed: 10-Apr-2019].
- [16] A. Iskandar, Iwan; Hidayat, "Analisa Quality of Service (QoS) Jaringan Internet Kampus (Studi Kasus: UIN Suska Riau)," *J. CoreIT*, vol. 1, no. 2, pp. 67–76, 2015.
- [17] E. Prasetyo, Eri; Hamzah, Amir; Sutanta, "Analisa Quality of Service (Qos) Kinerja Point To Point Protocol Over Ethernet (Pppoe) Dan Point To Point Tunneling Protocol (Pptp)," *J. Jarkom*, vol. 4, no. 1, 2017.
- [18] S. Cooper, "How To Fix Packet Loss," 2019. [Online]. Available: <https://www.comparitech.com/net-admin/minimize-packet-loss/>.
- [19] N. Mechatronics, "ATMega328P SMD." [Online]. Available:

<https://naylorlampmechatronics.com/atmel/262-atmega328p-smd.html>.
[Accessed: 10-Apr-2019].

- [20] Atmel, “ATmega328P 8-bit AVR Microcontroller with 32K Bytes In-System Programmable Flash DATASHEET,” pp. 1–294.
- [21] M. K. dan Informatika, *Rancangan Peraturan Menteri Komunikasi dan Informatika Republik Indonesia : Persyaratan Teknis Alat dan / atau Perangkat Telekomunikasi Low Power Wide Area*. 2018.
- [22] G. Description and K. E. Y. P. Features, “Rfm95/96/97/98 (w) .”
- [23] A. Hanneman, Robert; Riddle, Mark; J. Kposowa, *Basic Statistic for Social Research*. 2013.