

## DAFTAR PUSTAKA

- [1] Anwar, S. (2008). Variabel Tegangan Terhadap Hasil *Electropelating* Pada Alat Penyepuh Logam. Poli Rekayasa, 4, 42-49.
- [2] Perdana, S. P, Priambodo, A., Munarsyah, T., Pustaka, B. W., Widayatno, T. (2017). Penentuan Kondisi Operasi Elektropelating Krom yang Ramah Lingkungan. Jurnal Matematika dan Sains, 22, 5-8.
- [3] Indarto , Dwi (2009). Pengaruh Waktu Tahan Proses *Hot Dipping* Baja Karbon Rendah Terhadap Ketebalan Lapisan, Kekuatan Tarik dan Harga Impak Dengan Bahan Pelapis Alumunium. Skripsi thesis, Universitas Muhammadiyah Surakarta.
- [4] Selvakumar, N., Barshilia, H. C. (2011). *Review of physical vapor deposited (PVD) spectrally selective coatings for mid- and high- temperature solar thermal applications*. Solar Energy Materials & Solar Cells, 98, 1-23.
- [5] Suhendi, A., Munir, M. M., Suryamas, A. B., Nandiyanto, A. B. D., Ogi, T. and Okuyama, T. (2013). *Control of cone-jet geometry during electrospray by an electric current*. Adv. Powder Technol, 24, 532-536.
- [6] Weldzikarvina, Suhendi, A., Abrar. (2018). Studi Sistem Elektrospray Untuk Sintesis Partikel Polimer Berbasis Polietilen Glikol (PEG). e-Proceeding of Engineering, 5, 2380.
- [7] Wilm, M. S., Mann, M. (1994). *Electrospray and Taylor Cone Theory, Dole's Beam of macromolecules at last*. International Journal of Mass Spectrometry and Ion Processes, 136, 167-180.
- [8] Chiarot., P., R., Sullivan, P., and Mrad, R. B. *Electrospray from a droplet*. Experimental Thermal and Fluid Science, 37, 184-188.
- [9] Wei J., Liang P., Huang X. (2011). *Recent progress in electrodes for microbial fuel cells*. Bioresour. Technol. 102, 9335–9344.
- [10] Nadakatti, S., Tendulkar, M., Kadam, M. (2011). *Use of mesoporous conductive carbon black to enhance performance of activated carbon electrodes in capacitive deionization technology*. Desalination. 268. 182-188.

- [11] C. J. Hogan, K. M. Yun, D. R. Chen, I. W. Lenggoro, P. Biswas, and K. Okuyama, “*Controlled size polymer particle production via electrohydrodynamic atomization*,” *Colloids Surfaces A Physicochem. Eng. Asp.*, vol. 311, no. 1–3, pp. 67–76, 2007.
- [12] Castillo., J., L., Martin, S., Rodriguez-Perez., D., (2018). *Nanostuctured porous coatings via electrospray atomization and deposition of nanoparticle suspensions*. Journal of Aerosol Science. Vol 125. 148-163.
- [13] M. The and B. Braun, “Syringes & Needles Injekt ® Solo.”
- [14] Hikmah, F. N., (2012). Rancang Bangun Syringe Pump Berbasis Mikrokontroler ATMEGA8535 Dilengkapi Detektor Oklusi. Skripsi. Universitas Airlangga.
- [15] Junaedi, Nurmayady, D. (2012). Perancangan Pembangkit Tegangan Tinggi Direct Current Pada Sistem Elektrospinning.
- [16] Marno, Widianto, E., Sumarjo J., Santosa, A. (2018). Perancangan dan Pengembangan Sistem Elektrospinning sebagai Teknologi dalam Pembuatan Nanofiber. 18, 101-108.
- [17] Nandiyanto, A. B. D. (2011). *Progress in developing spray-drying methods for the production of controlled morphology particles: From the nanometer to submicrometer size ranges*. Adv. Powder Technol, 22, 1-19.
- [18] Kebarle, P., Verkerk, U., (2009) . *Electrospray : From Ions in Solution to Ions in the Gas Phase, What We Know Now*. Wiley InterScience. 1-18.
- [19] Tumimomor, F., Maddu, A., Pari, G., (2017). Pemanfaatan Karbon Aktif dari Bambu Sebagai Elektroda Superkapasitor. 17. 73-79.
- [20] Sembiring, G., (2009). Pengaruh Penambahan 0-10 wt% Carbon Black Terhadap Karakterisasi Komposit Epoxt/Grafit Sintesis Sebagai Material Pelat Bipolar *Polymer Electrolyte Membrane Fuel Cell*. Skripsi. FT, Program Studi Metalurgi dan Material, Universitas Indonesia.
- [21] *Surface tension values of some common test liquids for surface energy analysis.*  
<http://www.surface-tension.de/> (12 Juli 2019).

- [22] Permana, D., Haryadi, H., R., (2013). Evaluasi Penggunaan Metilen Biru Sebagai Mediator Elektron Pada *Mikrobial Fuel Cell* dengan Biokatalis *Acetobacter Aceti*. Molekul, Vol. 8. 78 – 88.