

## LIST OF TABLES

3.1	Specification of System . . . . .	21
3.2	Specification of antenna . . . . .	21
3.3	Initial dimensions of the antenna . . . . .	24
3.4	Bandwidth Result from Optimization $L_g$ . . . . .	30
3.5	Bandwidth Result from Optimization $W_g$ . . . . .	30
3.6	Bandwidth Result from Optimization $L_t$ . . . . .	31
3.7	Bandwidth Result from Optimization $W_t$ . . . . .	32
3.8	Bowtie antenna dimensions after optimization . . . . .	33
3.9	comparison of antenna dimension values before and after optimization	35
3.10	Bandwidth Result from the resistor value at element 1 is 33 ohm . .	39
3.11	Bandwidth Result from the resistor value at element 1 is 47 ohm . .	40
3.12	Bandwidth Result from the resistor value at element 1 is 75 ohm . .	41
3.13	Bandwidth Result from the resistor value at element 1 is 100 ohm .	42
3.14	Bandwidth Result from the resistor value at element 1 is 200 ohm .	43
3.15	Bandwidth Result from the resistor value at element 1 is 330 ohm .	44
3.16	Bandwidth Result from the resistor value at element 1 is 390 ohm .	45
3.17	Bandwidth Result from the resistor value at element 1 is 470 ohm .	46
3.18	Comparison Ringing Value . . . . .	47
3.19	Final Design . . . . .	53
3.20	Comparison between specification and simulation result . . . . .	54
4.1	Comparison table between bandwidth in simulation and measurement at 1200 - 2400 MHz . . . . .	60
4.2	Comparison table between bandwidth in simulation and measurement at 1300 - 2200 MHz . . . . .	61
4.3	Comparison table between bandwidth in simulation and measurement at 1200 - 2400 MHz . . . . .	66
4.4	Comparison table between bandwidth in simulation and measurement at 1300 - 2200 MHz . . . . .	67
4.5	Comparison table between bandwidth bowtie antenna with and without resistive loaded in first range frequency . . . . .	69
4.6	Comparison table between bandwidth bowtie antenna with and without resistive loaded in second range frequency . . . . .	70

4.7 Comparison between ringing level on several distance . . . . . 86