# DAFTAR PUSTAKA


[1] Y. Li, L. Zhang, X. Tan, and B. Cao, "An advanced spectrum allocation algorithm for the across-cell D2D communication in LTE network with higher throughput," vol. 13, no. 4, pp. 30–37, 2016.

[2] D. Camps-Mur, A. Garcia-Saavedra, and P. Serrano, "Device-to-device communications with Wi-Fi Direct: overview and experimentation," *IEEE Wirel. Commun.*, vol. 20, no. 3, pp. 96–104, 2013.

[3] S. Hara and R. Prasad, *Multicarrier Techniques for 4G Mobile Communications*. Artech House, 2003.

[4] A. Asadi, Q. Wang, and V. Mancuso, "A survey on device-to-device communication in cellular networks," *IEEE Commun. Surv. Tutorials*, vol. 16, no. 4, pp. 1801–1819, 2014.

[5] T.-H. Tan, B.-A. Chen, and Y.-F. Huang, "Performance of Resource Allocation in Device-toDevice Communication Systems Based on Particle Swarm Optimization," *Appl. Sci.*, vol. 8, no. 8, p. 1271, 2018.

[6] L. Wang, T. Peng, Y. Yang, and W. Wang, "Interference Constrained D2D Communication with Relay Underlaying Cellular Networks," *IEEE*, 2013.

[7] A. F. S. Admaja, "Kajian Awal 5G Indonesia (5G Indonesia Early Preview)," *Bul. Pos dan Telekomun.*, vol. 13, no. 2, p. 97, 2015.

[8] ITU-R, "'IMT Vision – Framework and overall objectives of the future development of IMT for 2020 and beyond,'" *Itu-R M.2083-0*, vol. 0, p. http://www.itu.int/publ/R-REC/en, 2015.

[9] R. AliHemmati, M. Dong, B. Liang, G. Boudreau, and S. H. Seyedmehdi, "Multi-Channel Resource Allocation Toward Ergodic Rate Maximization for Underlay Device-to-Device Communications," *IEEE Trans. Wirel. Commun.*, vol. 17, no. 2, pp. 1011–1025, 2018.

[10] T. Doumi *et al.*, "LTE for public safety networks," *IEEE Commun. Mag.*, vol. 51, no. 2, pp. 106–112, 2013.

[11] L. Wang and H. Tang, *Device-to-Device Communications in Cellular Networks*, 1st ed. Springer International Publishing, 2016.

[12] Anristu Company, "LTE Resource Guide," *Test. Futur. LTE Resour. Guid.*, p. 17, 2009.

[13] M. T. Islam, A. E. M. Taha, S. Akl, and S. Choudhury, “A two-phase auction-based fair resource allocation for underlaying D2D communications,” *2016 IEEE Int. Conf. Commun. ICC 2016*, 2016.

[14] J. Kennedy and R. Eberhart, “Prognostic evaluation of abdominal echography in typhoid fever,” *G. Mal. Infett. Parassit.*, vol. 46, no. 10, pp. 1942–1948, 1994.

[15] B. Santosa, “Tutorial Particle Swarm Optimization,” *academia.edu*, 2006.

[16] L. Su, P. Wang, and F. Liu, “Particle swarm optimization based resource block allocation algorithm for downlink LTE systems,” *IEEE*, pp. 970–974, 2012.

[17] I. G. Fraimis and S. A. Kotsopoulos, “QoS-based proportional fair allocation algorithm for OFDMA wireless cellular systems,” *IEEE Commun. Lett.*, vol. 15, no. 10, pp. 1091–1093, 2011.

[18] V. S. Widhi Prabowo, A. Fahmi, N. M. Adriansyah, and N. Andini, “Energy efficient resources allocations for wireless communication systems,” *TELKOMNIKA (Telecommunication Comput. Electron. Control.*, vol. 17, no. 4, p. 1625, 2019.

[19] R. Jain, D. Chiu, and W. Hawe, “A Quantitative Measure Of Fairness And Discrimination For Resource Allocation In Shared Computer Systems,” no. June 2014, 1998.

[20] Q. Wang, T. Chen, and H. L. Liu, “Resource Allocation for D2D Underlay Communication Systems Using PSO,” *Proc. - 13th Int. Conf. Comput. Intell. Secur. CIS 2017*, vol. 2018–Janua, pp. 202–206, 2018.

[21] Y. Tao, J. Sun, and S. Shao, “Radio resource allocation based on greedy algorithm and successive interference cancellation in Device-to-Device (D2D) communication,” *IET Conf. Publ.*, vol. 2013, no. 618 CP, pp. 452–458, 2013.