

## DAFTAR PUSTAKA

- Agrawal, S., Gaur, M. kumar, Kasdekar, D. kumar, & Agrawal, S. (2018). Optimization of machining parameters of hard porcelain on a CNC machine by Taguchi-and RSM method. *International Journal of Engineering, Science and Technology*, 10(1), 13. <https://doi.org/10.4314/ijest.v10i1.2>
- Amini, S., Soleimanimehr, H., Nategh, M. J., Abudollah, A., & Sadeghi, M. H. (2008). FEM analysis of ultrasonic-vibration-assisted turning and the vibratory tool. *Journal of Materials Processing Technology*, 201(1–3), 43–47. <https://doi.org/10.1016/j.jmatprotec.2007.11.271>
- Asiltürk, I., & Akkuş, H. (2011). Determining the effect of cutting parameters on surface roughness in hard turning using the Taguchi method. *Measurement: Journal of the International Measurement Confederation*, 44(9), 1697–1704. <https://doi.org/10.1016/j.measurement.2011.07.003>
- Asiltürk, I., & Çunkaş, M. (2011). Modeling and prediction of surface roughness in turning operations using artificial neural network and multiple regression method. *Expert Systems with Applications*, 38(5), 5826–5832. <https://doi.org/10.1016/j.eswa.2010.11.041>
- Bademlioglu, A. H., Canbolat, A. S., Yamankaradeniz, N., & Kaynakli, O. (2018). Investigation of parameters affecting Organic Rankine Cycle efficiency by using Taguchi and ANOVA methods. *Applied Thermal Engineering*, 145, 221–228. <https://doi.org/10.1016/j.applthermaleng.2018.09.032>
- Chethan, Y. D., Ravindra, H. V., & Krishnegowda, Y. T. (2019). Optimization of machining parameters in turning Nimonic-75 using machine vision and acoustic emission signals by Taguchi technique. *Measurement: Journal of the International Measurement Confederation*, 144, 144–154. <https://doi.org/10.1016/j.measurement.2019.05.035>
- David, S., Damayanti, D. D., & Eka, D. S. (2016). Optimasi Sensor Kamera pada Proses Identifikasi Warna dengan Pengolahan Citra Menggunakan Design Of Experiment. *E-Proceeding Of Engineering*, 3(2), 8.

<https://doi.org/doi:10.4324/9780203852484>

- Deepanraj, B., Sivasubramanian, V., & Jayaraj, S. (2017). Multi-response optimization of process parameters in biogas production from food waste using Taguchi – Grey relational analysis. *Energy Conversion and Management*, *141*, 429–438. <https://doi.org/10.1016/j.enconman.2016.12.013>
- Gadekula, R. K., Potta, M., Kamisetty, D., Yarava, U. K., Anand, P., & Dondapati, R. S. (2018). Investigation on Parametric Process Optimization of HCHCR in CNC Turning Machine Using Taguchi Technique. *Materials Today: Proceedings*, *5*(14), 28446–28453. <https://doi.org/10.1016/j.matpr.2018.10.131>
- Ghani, J. A., Che Haron, C. H., Kasim, M. S., Sulaiman, M. A., & Tomadi, S. H. (2016). Wear mechanism of coated and uncoated carbide cutting tool in machining process. *Journal of Materials Research*, *31*(13), 1873–1879. <https://doi.org/10.1557/jmr.2015.382>
- Krishankant, Taneja, J., Bector, M., & Kumar, R. (2012). Application of Taguchi Method for Optimizing Turning Process by the Effects of Machining Parameters. *International Journal of Engineering and Advanced Technology (IJEAT)*, *(2)*, 263. Retrieved from <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.674.7465&rep=rep1&type=pdf>
- Krishna Madhavi, S., Sreeramulu, D., & Venkatesh, M. (2017). Evaluation of Optimum Turning Process of Process Parameters Using DOE and PCA Taguchi Method. *Materials Today: Proceedings*, *4*(2), 1937–1946. <https://doi.org/10.1016/j.matpr.2017.02.039>
- Kumar, N. S., Shetty, A., Shetty, A., Ananth, K., & Shetty, H. (2012). Effect of spindle speed and feed rate on surface roughness of carbon steels in CNC turning. *Procedia Engineering*, *38*(Icmoc), 691–697. <https://doi.org/10.1016/j.proeng.2012.06.087>
- M'Saoubi, R., Outeiro, J. C., Chandrasekaran, H., Dillon, O. W., & Jawahir, I. S. (2008). A review of surface integrity in machining and its impact on functional

- performance and life of machined products. *International Journal of Sustainable Manufacturing*, 1(1–2), 203–236. <https://doi.org/10.1504/IJSM.2008.019234>
- Mahajan, S., & Bapat, P. (2012). Specialized Noise Control Materials in the Automotive Industry. *Ijese.Org*, (1), 263–274. Retrieved from <http://www.ijese.org/attachments/File/v2i1/A0582112113.pdf>
- Mukherjee, I., & Ray, P. K. (2006). A review of optimization techniques in metal cutting processes. *Computers and Industrial Engineering*, 50(1–2), 15–34. <https://doi.org/10.1016/j.cie.2005.10.001>
- Nahm, F. S. (2016). Nonparametric statistical tests for the continuous data: The basic concept and the practical use. *Korean Journal of Anesthesiology*, 69(1), 8–14. <https://doi.org/10.4097/kjae.2016.69.1.8>
- P. P. Shirpurkar, S.R. Bobde, V.V.Patil, B. N. K. (2012). Optimization of Turning Process Parameters by Using Tool Inserts- A Review. *International Journal of Engineering and Innovative Technology (IJEIT)*, 2(6), 216–223. Retrieved from [http://www.ijeit.com/vol 2/Issue 6/IJEIT1412201212\\_40.pdf](http://www.ijeit.com/vol 2/Issue 6/IJEIT1412201212_40.pdf)
- Pathak, A. D., Warghane, R. S., & Deokar, S. U. (2018). Optimization of cutting parameters in Dry Turning of AISI A2 Tool Steel using Carbide Tool by Taguchi Based Fuzzy Logics. *Materials Today: Proceedings*, 5(2), 5082–5090. <https://doi.org/10.1016/j.matpr.2017.12.087>
- Pradhan, M. K. (2013). Estimating the effect of process parameters on MRR, TWR and radial overcut of EDMed AISI D2 tool steel by RSM and GRA coupled with PCA. *International Journal of Advanced Manufacturing Technology*, 68(1–4), 591–605. <https://doi.org/10.1007/s00170-013-4780-9>
- Qehaja, N., Jakupi, K., Bunjaku, A., Bruçi, M., & Osmani, H. (2015). Effect of machining parameters and machining time on surface roughness in dry turning process. *Procedia Engineering*, 100(January), 135–140. <https://doi.org/10.1016/j.proeng.2015.01.351>
- Rachmat, H., Ibrahim, M. R., & Hasan, S. (2017). Preliminary Investigation of

Parametric Optimization on Turning Process Using UVAT Tool Holder Based on Taguchi Method. *MATEC Web of Conferences*, 135. <https://doi.org/10.1051/mateconf/201713500016>

Radha Krishnan, B., & Ramesh, M. (2019). Optimization of machining process parameters in CNC turning process of IS2062 E250 Steel using coated carbide cutting tool. *Materials Today: Proceedings*, (xxxx). <https://doi.org/10.1016/j.matpr.2019.05.460>

Raul. (2016). POTONG PADA MESIN BUBUT TERHADAP TINGKAT KEKASARAN PERMUKAAN BENDA KERJA ST 41 Oleh : *Jurnal Teknik Mesin*, 24(1), 1–9.

Sajjady, S. A., Nouri Hossein Abadi, H., Amini, S., & Nosouhi, R. (2016). Analytical and experimental study of topography of surface texture in ultrasonic vibration assisted turning. *Materials and Design*, 93, 311–323. <https://doi.org/10.1016/j.matdes.2015.12.119>

Sharma, V., & Pandey, P. M. (2016). Recent advances in ultrasonic assisted turning: A step towards sustainability. *Cogent Engineering*, 3(1). <https://doi.org/10.1080/23311916.2016.1222776>

Sidi, P., & Wahyudi, M. (2013). Aplikasi Metoda Taguchi Untuk Mengetahui Optimasi Kebulatan Pada Proses Bubut Cnc. *Rekayasa Mesin*, 4(2), pp.101-108.

Silalahi, S. A. F. (2014). Kondisi Industri Manufaktur Indonesia Dalam Menghadapi Globalisasi. *Jurnal Ekonomi Dan Kebijakan Publik*, 5(1), 1–13.

Sivareddy, D. V., Krishna, P. V., Gopal, A. V., & Raz, C. L. P. (2018). Parameter optimisation in vibration assisted turning of Ti6Al4V alloy using ANOVA and grey relational analysis. *International Journal of Automotive and Mechanical Engineering*, 15(3), 5400–5420. <https://doi.org/10.15282/ijame.15.3.2018.1.0416>

Sivareddy, D. V., Krishna, P. V., Gopal, A. V., & Raz, C. L. P. (2019). Parameter Optimisation in Vibration Assisted Turning of Ti6Al4V Alloy using ANOVA

and Grey Relational Analysis. *Journal of Chemical Information and Modeling*, 53(9), 1689–1699.  
<https://doi.org/10.1017/CBO9781107415324.004>

Thamizhmanii, S., & Hasan, S. (2006). Analyses of roughness, forces and wear in turning gray cast iron. *Journal of Achievements in Materials ...*, 17(1), 401–404. Retrieved from [http://jamme.acmsse.h2.pl/papers\\_amme06/1224.pdf](http://jamme.acmsse.h2.pl/papers_amme06/1224.pdf) [http://www.journalamme.org/papers\\_amme06/1224.pdf](http://www.journalamme.org/papers_amme06/1224.pdf)

Tzeng, C. J., Lin, Y. H., Yang, Y. K., & Jeng, M. C. (2009). Optimization of turning operations with multiple performance characteristics using the Taguchi method and Grey relational analysis. *Journal of Materials Processing Technology*, 209(6), 2753–2759.  
<https://doi.org/10.1016/j.jmatprotec.2008.06.046>

Vivekananda, K., Arka, G. N., & Sahoo, S. K. (2014). Finite Element Analysis and Process Parameters Optimization of Ultrasonic Vibration Assisted Turning (UVT). *Procedia Materials Science*, 6(Icmpc), 1906–1914.  
<https://doi.org/10.1016/j.mspro.2014.07.223>

Yasa Utama, F., & Hartutuk Ningsih, T. (2016). Optimasi Parameter Pemesinan dengan Proses Bubut pada Respon Kekasaran dan Kekerasan Permukaan Material S45-C Menggunakan Metode Taguchi - Grey - Fuzzy. *Rekayasa Energi Manufaktur*, 1(1). <https://doi.org/10.21070/r.e.m.v1i1.169>

Zhang, S. J., To, S., Wang, S. J., & Zhu, Z. W. (2015). A review of surface roughness generation in ultra-precision machining. *International Journal of Machine Tools and Manufacture*, 91, 76–95.  
<https://doi.org/10.1016/j.ijmachtools.2015.02.001>

Zou, P., Xu, Y., He, Y., Chen, M., & Wu, H. (2015). Experimental investigation of ultrasonic vibration assisted turning of 304 austenitic stainless steel. *Shock and Vibration*, 2015. <https://doi.org/10.1155/2015/817598>

