

## LIST OF FIGURES

2.1	Network model of IEEE 802.11ah adopted from [12] . . . . .	5
2.2	Channelization in US . . . . .	6
2.3	MAC Architecture adopted from [16] . . . . .	6
2.4	AID Basic frame structure adopted from [22] . . . . .	9
2.5	DTIM and TIM Structures . . . . .	10
2.6	Adoption of IEEE 802.11ah in the United States . . . . .	12
2.7	Adoption of IEEE 802.11ah in Japan . . . . .	13
2.8	Adoption of IEEE 802.11ah in South Korea . . . . .	13
2.9	Adoption of IEEE 802.11ah in Europe . . . . .	13
2.10	Adoption of IEEE 802.11ah in China . . . . .	14
2.11	Adoption of IEEE 802.11ah in Singapore . . . . .	14
2.12	Indonesia's sub GHz Frequency Allocation . . . . .	16
2.13	Adoption for GSM Technology . . . . .	17
3.1	Research Framework . . . . .	22
3.2	Simulation Model . . . . .	23
3.3	Simulation Flowchart Design of 802.11ah . . . . .	24
3.4	Node Simulation in NS3 . . . . .	26
3.5	Simulation Scenario . . . . .	28
3.6	Bandung Raya Captures Map . . . . .	28
4.1	Throughput on 1 MHz Bandwidth . . . . .	31
4.2	Throughput on 2 MHz Bandwidth . . . . .	32
4.3	Throughput Comparison . . . . .	33
4.4	Delay on 1 MHz Bandwidth . . . . .	34
4.5	Delay on 2 MHz Bandwidth . . . . .	35
4.6	Delay Comparison . . . . .	35
4.7	Energy on 1 MHz Bandwidth . . . . .	37
4.8	Energy on 2 MHz Bandwidth . . . . .	37
4.9	Energy Comparison . . . . .	38
4.10	Simulator Setup for RAW Slot 20 . . . . .	39
4.11	Throughput with RAW Slot 20 . . . . .	40
4.12	Delay with RAW Slot 20 . . . . .	41
4.13	Energy with RAW Slot 20 . . . . .	41