

**List of Figures**

1 Damaged Road . . . . . 1

2 Rigid and Flexible Pavement Load DistributionOverall [1] . . . . . 5

3 Illustration of how GPS works[15] . . . . . 7

4 Coordinate system (relative to a device [13]) . . . . . 8

5 Raw Threshold . . . . . 9

6 Scenario Design . . . . . 11

7 Phone Position . . . . . 12

8 Application Flow Chart . . . . . 13

9 Phone Position at Scooter . . . . . 16

10 Soekarno Hatta street . . . . . 17

11 Example average Chart from Soekarno Hatta street . . . . . 17

12 Application Running . . . . . 19

13 Application Stop and Save . . . . . 20

14 Make Data and Open Raw Data . . . . . 20

15 Result Data . . . . . 21

16 Batununggal, Sukapura, Sukabirus street . . . . . 22

17 Result table Batununggal using alpha 0.95 . . . . . 23

18 Result table Batununggal using alpha 0.90 . . . . . 23

19 Result table Batununggal using alpha 0.85 . . . . . 24

20 Result table Sukapura using alpha 0.95 . . . . . 25

21 Result table Sukapura using alpha 0.90 . . . . . 25

22 Result table Sukapura using alpha 0.85 . . . . . 26

23 Result table Sukabirus using alpha 0.95 . . . . . 27

24 Result table Sukabirus using alpha 0.90 . . . . . 28

25 Result table Sukabirus using alpha 0.85 . . . . . 28

26 Result Batununggal using 0.95, 0.90, 0.85 threshold . . . . . 29

27 Result Sukapura using 0.95, 0.90, 0.85 threshold . . . . . 29

28 Result Sukabirus using 0.95, 0.90, 0.85 threshold . . . . . 30