

DAFTAR SINGKATAN

3GPP	: 3rd Generation Partnership Project Long Term Evolution
LTE-A	: Long Term Evolution Advanced
BTS	: Base Transceiver Station
eNodeB	: Evolved Node B
KPI	: Key Performance Indicator
RSRP	: Reference Signal Received Power
CINR	: Carrier to Noise Ratio
DL	: Downlink
UL	: Uplink
UE	: User Equipment
eICIC	: Enhanced Inter-cell Interference Coordination
ABS	: Almost Blank <i>Subframe</i>
RPS	: Radiowave Propagation Simulation
RF	: Radio Frekuensi
EPC	: Evolved Packet Core
E-UTRAN	: Evolved Universal Terrestrial Radio Access Network
FDD	: Frequency Division Duplex
HetNet	: Heterogeneous Network
MAPL	: Maximum Allowable Path Loss
MIMO	: Multiple Input Multiple Output
LPN	: Low Power Node
RRH	: Remote Radio Head
NRB	: Number of Resource Block
RSSI	: Received Signal Strength Indicator
QOS	: Quality of Service
GF	: Growth factor
PL	: Penetration Loss
BL	: Body Loss
IM	: Interference Margin
UP	: Usia Produktif
MSO	: Market Share Operator
LP	: LTE Penetration