

References

- [1] Y. Chen and Y. Xue, "A Deep Learning Approach to Human Activity Recognition Based on Single Accelerometer," *Proc. - 2015 IEEE Int. Conf. Syst. Man, Cybern. SMC 2015*, pp. 1488–1492, 2015, doi: 10.1109/SMC.2015.263.
- [2] S. Ha and S. Choi, "Convolutional Neural Networks for Human Activity Recognition using Multiple Accelerometer and Gyroscope Sensors," *IEEE*, 2016, doi: 10.3390/informatics5020026.
- [3] L. Chen, C. D. Nugent, and H. Wang, "A knowledge-driven approach to activity recognition in smart homes," *IEEE Trans. Knowl. Data Eng.*, vol. 24, no. 6, pp. 961–974, 2012, doi: 10.1109/TKDE.2011.51.
- [4] L. Wang, W. Li, and L. Van Gool, "Appearance-and-Relation Networks for Video Classification," *Proc. IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit.*, pp. 1430–1439, 2018, doi: 10.1109/CVPR.2018.00155.
- [5] M. S. Ryoo, "Human activity prediction: Early recognition of ongoing activities from streaming videos," *Proc. IEEE Int. Conf. Comput. Vis.*, no. Iccv, pp. 1036–1043, 2011, doi: 10.1109/ICCV.2011.6126349.
- [6] Y. Kim and T. Moon, "Human detection and activity classification based on micro-doppler signatures using deep convolutional neural networks," *IEEE Geosci. Remote Sens. Lett.*, vol. 13, no. 1, pp. 8–12, 2016, doi: 10.1109/LGRS.2015.2491329.
- [7] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," *Proc. IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit.*, vol. 2016-Decem, pp. 770–778, 2016, doi: 10.1109/CVPR.2016.90.
- [8] L. N. Smith, "Cyclical learning rates for training neural networks," *Proc. - 2017 IEEE Winter Conf. Appl. Comput. Vision, WACV 2017*, no. April 2015, pp. 464–472, 2017, doi: 10.1109/WACV.2017.58.
- [9] J. Preis, M. Kessel, M. Werner, and C. Linnhoff-Popien, "Gait Recognition with Kinect," *Work. Kinect Pervasive Comput. Pervasive 2012*, no. July 2015, pp. 1–5, 2012, [Online]. Available: http://noggogg.com/pervasivekinect/wp-content/uploads/2012/06/Preis_GaitRecognition.pdf.
- [10] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, "Dropout: A Simple Way to Prevent Neural Networks from Overfitting," *J. Mach. Learn. Res.* 15, vol. 299, no. 3–4, pp. 345–350, 2014, doi: 10.1016/0370-2693(93)90272-J.
- [11] Y. N. Dauphin, H. De Vries, and Y. Bengio, "RMSProp and equilibrated adaptive learning rates for non-convex optimization," *Adv. Neural Inf. Process. Syst.*, vol. 2015-Janua, pp. 1504–1512, 2015.
- [12] C. M. Bishop, *Pattern Recognition and Machine Learning*, vol. 27, no. 1. 2004.
- [13] Q. Kong, Z. Wu, Z. Deng, M. Klinkigt, B. Tong, and T. Murakami, "MMAct: A Large-Scale Dataset for Cross Modal Human Action Understanding," *IEEE Int. Conf. Comput. Vis.*, pp. 8658–8667, 2019, [Online]. Available: http://openaccess.thecvf.com/content_ICCV_2019/papers/Kong_MMAct_A_Large-Scale_Dataset_for_Cross_Modal_Human_Action_Understanding_ICCV_2019_paper.pdf.