

CONTENTS

APPROVAL PAGE

LEMBAR PERNYATAAN ORISINALITAS

| | |
|---|-------------|
| ABSTRACT | iv |
| Contents | v |
| List of Tables | vii |
| List of Figures | viii |
| DAFTAR SINGKATAN | ix |
| I INTRODUCTION | 1 |
| 1.1 Background | 1 |
| 1.2 Problem Formulation | 2 |
| 1.3 Objectives | 2 |
| 1.4 Scope of Problem | 2 |
| 1.5 Method of Research | 2 |
| 1.6 Writing Systematics | 3 |
| 1.7 Milestones | 3 |
| II BASIC CONCEPT | 4 |
| 2.1 GNS3 | 4 |
| 2.2 Routing Overview | 5 |
| 2.2.1 OSPF | 5 |
| 2.3 Network Function Virtualization | 7 |
| 2.3.1 Free Range Routing | 7 |
| 2.3.2 BIRD Routing Daemon | 9 |
| 2.4 Convergence Time | 12 |
| 2.5 Quality of Service | 13 |
| III MODEL AND SYSTEM DESIGN | 15 |
| 3.1 Simulation Setup | 15 |

| | | |
|---------------------|--|-----------|
| 3.2 | Simulation Process | 16 |
| 3.2.1 | Convergence Time | 17 |
| 3.2.2 | QoS measurement | 19 |
| 3.3 | Topology | 19 |
| 3.4 | Installation and configuration | 21 |
| 3.4.1 | FRRouting | 21 |
| 3.4.2 | BIRD | 24 |
| 3.4.3 | Host | 26 |
| IV | RESULT AND ANALYSIS | 27 |
| 4.1 | Convergence Time | 27 |
| 4.1.1 | Convergence time of FRR in QEMU | 27 |
| 4.1.2 | Convergence Time of FRR and BIRD in VM | 28 |
| 4.2 | Packet Loss | 31 |
| 4.3 | Jitter | 32 |
| 4.4 | Throughput | 32 |
| 4.5 | Delay | 33 |
| 4.6 | Traffic Overhead | 34 |
| V | CONCLUSIONS AND SUGGESTIONS | 35 |
| 5.1 | Conclusions | 35 |
| 5.2 | Sugesstion | 36 |
| Bibliography | | 37 |
| LAMPIRAN | | 1 |