

## DAFTAR GAMBAR

|      |  |    |
|------|--|----|
| 2.1  | Perbandingan arsitektur jaringan tradisional dan SDN [18]. . . . .           | 5  |
| 2.2  | Lapisan Arsitektur <i>Software Defined Networking</i> (SDN) [20] . . . . .   | 6  |
| 2.3  | Komponen pada <i>OpenFlow switch</i> [24] . . . . .                          | 8  |
| 2.4  | Isi Flow table pada <i>OpenFlow switch</i> [25] . . . . .                    | 8  |
| 2.5  | Perbandingan switch konvensional dengan P4-defined switch [28] . .           | 9  |
| 2.6  | <i>Protocol-Independent Switch Architecture</i> PISA [28] . . . . .          | 10 |
| 2.7  | Arsitektur P4Runtime [31] . . . . .  | 11 |
| 2.8  | Komponen sistem ONOS [37] . . . . .  | 13 |
| 2.9  | Pendekatan <i>Bottom-up programming</i> [39] . . . . .                       | 14 |
| 2.10 | Pendekatan <i>Top-down Programming</i> [39]. . . . .                         | 15 |
| 2.11 | Komponen di Sistem SNMP [43] . . . . .                                       | 16 |
| 2.12 | Diagram proses SNMP [44] . . . . .   | 16 |
| 2.13 | Format <i>header</i> paket SNMPv1 dan SNMPv2 [43] . . . . .                  | 17 |
| 2.14 | Format <i>header</i> paket SNMPv3 [43] . . . . .                             | 17 |
| 2.15 | Contoh penggunaan INT menggunakan mode INT-MD[48] . . . . .                  | 19 |
| 2.16 | Jenis mode operasi dalam INT [47] . . . . .                                  | 22 |
| 2.17 | <i>Header</i> format INT-MX[47] . . . . .                                    | 23 |
| 2.18 | <i>Header</i> format INT-MD[47] . . . . .                                    | 23 |
| 3.1  | Gambaran umum sistem . . . . .   | 24 |
| 3.2  | Implementasi arsitektur kebutuhan sistem . . . . .                           | 26 |
| 3.3  | Diagram blok sistem . . . . .  | 27 |
| 3.4  | Implementasi topology sistem . . . . .                                       | 29 |
| 3.5  | Topologi pengujian <i>storage overhead idle condition</i> . . . . .          | 30 |
| 3.6  | Topologi pengujian <i>storage overhead active</i> . . . . .                  | 31 |
| 3.7  | Topologi pengujian <i>storage overhead with background traffic</i> . . . . . | 32 |
| 4.1  | <i>Storage overhead idle</i> . . . . .                                       | 33 |
| 4.2  | <i>Storage overhead active</i> . . . . .                                     | 34 |
| 4.3  | <i>Storage overhead with background traffic</i> . . . . .                    | 35 |
| 4.4  | <i>Storage overhead with background traffic</i> . . . . .                    | 36 |
| 4.5  | Active Overhead . . . . .  | 37 |
| 4.6  | Hop latency source switch . . . . .  | 38 |

|     |                                      |    |
|-----|--------------------------------------|----|
| 4.7 | Hop latency transit switch . . . . . | 38 |
| 4.8 | Hop latency sink switch . . . . .    | 39 |
| 4.9 | Total latency . . . . .              | 39 |