

## DAFTAR TABEL

Tabel 2. 1 <i>Bandwidth supported by LTE</i> .....	17
Tabel 2. 2 MAPL <i>uplink</i> 1800 MHz.....	20
Tabel 2. 3 MAPL <i>uplink</i> 2100 MHz.....	21
Tabel 2. 4 MAPL <i>downlink</i> 1800 MHz.....	21
Tabel 2. 5 MAPL <i>downlink</i> 2100 MHz.....	22
Tabel 2. 6 Spesifikasi model propagasi Cost-231 .....	23
Tabel 2. 7 <i>Service model parameter</i> .....	24
Tabel 2. 8 <i>Traffic model parameter</i> .....	25
Tabel 2. 9 <i>Peak Average Ratio (PAR)</i> .....	25
Tabel 2. 10 <i>Cell capacity</i> .....	26
Tabel 2. 11 Standar nilai RSRP Operator XL .....	27
Tabel 2. 12 Standar nilai SINR Operator XL.....	28
Tabel 2. 13 Standar nilai <i>throughput</i> Operator XL .....	28
Tabel 4. 1 Perbandingan rata-rata antar skenario .....	58
Tabel 4. 2 Perbandingan hasil simulasi RSRP .....	58
Tabel 4. 3 Perbandingan hasil simulasi SINR.....	59
Tabel 4. 4 Perbandingan hasil simulasi <i>throughput downlink</i> .....	60
Tabel 4. 5 Perbandingan hasil simulasi <i>throughput uplink</i> .....	61
Tabel 4. 6 Perbandingan hasil simulasi skenario non-CA dengan CA_3_3B.....	61
Tabel 4. 7 Perbandingan hasil simulasi skenario non-CA dengan CA_3A_1.....	61
Tabel 4. 8 Perbandingan hasil simulasi skenario CA_3_3B dengan CA_3A_1 .....	62