

# CONTENTS

## ENDORSEMENT LETTER

## STATEMENT OF ORIGINALITY

## ABSTRACT iv

## THANK YOU NOTE v

## Preface vi

## Contents vii

## List of Figures x

## List of Tables xii

## LIST OF ABBREVIATIONS xiii

## I INTRODUCTION 1

1.1 Background . . . . . 1

1.2 Formulation of Problem . . . . . 2

1.3 Purpose of Research . . . . . 2

1.4 Scope of Problem . . . . . 2

1.5 Research Method . . . . . 3

1.6 Thesis Organization . . . . . 3

## II BASIC CONCEPT 4

2.1 Internet of Things (IoT) . . . . . 4

2.2 Bluetooth . . . . . 4

2.2.1 Bluetooth Protocol Stacks . . . . . 5

2.2.1.1 The Baseband Layer . . . . . 5

2.2.1.2 The Link Controller and Link Manager . . . . . 6

2.2.1.3 The HCI Interface . . . . . 7

2.2.1.4 The L2CAP Layer . . . . . 7

2.2.1.5 The Service Discovery Protocol . . . . . 7

2.2.1.6 The RFCOMM Layer . . . . . 8

|         |  |    |
|---------|--|----|
| 2.3     | Bluetooth Low Energy (BLE) . . . . .                         | 8  |
| 2.3.1   | BLE Protocol Stack . . . . .                                 | 9  |
| 2.3.1.1 | Host Protocol . . . . .                                      | 9  |
| 2.3.1.2 | Controller Protocol . . . . .                                | 10 |
| 2.3.1.3 | Security System of BLE . . . . .                             | 11 |
| 2.4     | Authentication Security System . . . . .                     | 13 |
| 2.4.1   | Token-Based Authentication . . . . .                         | 13 |
| 2.4.2   | Token-Based Authentication on Bluetooth Low Energy . . . . . | 14 |
| 2.5     | Packet Sniffing . . . . .                                    | 15 |
| 2.5.1   | Bluetooth Packet Sniffing . . . . .                          | 16 |

**III TOKEN AUTHENTICATION MECHANISM FOR BLUETOOTH  
LOW ENERGY (BLE) NETWORKS 17**

|       |   |    |
|-------|---|----|
| 3.1   | Design System . . . . .   | 17 |
| 3.1.1 | Temperature Sensor System Design . . . . .  | 18 |
| 3.1.2 | Token Authentication Mechanism for BLE based Temperature Sensor System Design . . . . . | 19 |
| 3.1.3 | Token Authentication Testing with Packet Sniffing . . . . .                             | 20 |
| 3.2   | Tools Specification . . . . .   | 21 |
| 3.2.1 | Hardware . . . . .  | 21 |
| 3.2.2 | Software . . . . .  | 25 |
| 3.3   | Implementation of The System . . . . .  | 28 |
| 3.3.1 | Testing Scenario . . . . .  | 29 |
| 3.3.2 | Temperature Sensor Configuration . . . . .  | 30 |
| 3.3.3 | Ubertooth ONE Configuration . . . . .   | 31 |
| 3.3.4 | Application Interface . . . . .   | 33 |
| 3.4   | Calibration Data Aggregation . . . . .  | 35 |
| 3.4.1 | Throughput . . . . .  | 35 |
| 3.4.2 | Delay . . . . .   | 35 |
| 3.4.3 | Jitter . . . . .  | 36 |

**IV EVALUATION 37**

|       |  |    |
|-------|--|----|
| 4.1   | Capturing Process . . . . .                      | 37 |
| 4.2   | Connectivity Analysis . . . . .                  | 40 |
| 4.3   | Throughput, Delay, and Jitter Analysis . . . . . | 43 |
| 4.4   | Authentication Analysis . . . . .                | 44 |
| 4.5   | Device Capabilities Analysis . . . . .           | 51 |
| 4.5.1 | Room Temperature . . . . .                       | 51 |

|          |                                    |           |
|----------|------------------------------------|-----------|
| 4.5.2    | Body Temperature . . . . .         | 54        |
| 4.5.3    | Extreme Temperature . . . . .      | 56        |
| <b>V</b> | <b>CONCLUSION</b>                  | <b>60</b> |
| 5.1      | Conclusions . . . . .              | 60        |
| 5.2      | Suggestions . . . . .              | 60        |
|          | <b>Bibliography</b>                | <b>62</b> |
|          | <b>APPENDIX</b>                    | <b>1</b>  |
| <b>A</b> | <b>TABLE RESULTS OF EXPERIMENT</b> | <b>1</b>  |
| <b>B</b> | <b>CODING</b>                      | <b>3</b>  |
| <b>C</b> | <b>IMAGE RESULTS OF EXPERIMENT</b> | <b>1</b>  |