

## DAFTAR ISI

	<b>Halaman</b>
LEMBAR PENGESAHAN	i
ABSTRAK	ii
ABSTRACT	iii
KATA PENGANTAR	iv
DAFTAR ISI	v
DAFTAR GAMBAR	viii
<b>BAB I PENDAHULUAN</b>	
1.1 Latar Belakang	1
1.2 Tujuan Penelitian	2
1.3 Rumusan Masalah	2
1.4 Batasan Masalah	2
1.5 Metodologi Penelitian	2
1.6 Sistematika Penulisan	3
<b>BAB II DASAR TEORI <i>LINK BUDGET</i> SATELIT BERSTANDAR <i>SATELLITE REQUIREMENT L-BAND</i></b>	
2.1 <i>Link Budget</i> Satelit	4
2.1.1 Parameter <i>Link Budget</i> Satelit	5
2.1.1.1 Gain Antena	5
2.1.1.2 Gain to Noise Temperatur	5
2.1.1.3 <i>Losses</i>	6
2.1.1.2 Daya Carrier to Noise Ratio	6
2.1.1.4 Daya Carrier to Noise Temperatur	7
2.2. <i>Satellite Requirement L-Band</i>	8
<b>BAB III PROSEDUR SIMULASI <i>LINK BUDGET</i> SATELIT BERSTANDAR <i>SATELLITE REQUIREMENT L-BAND</i></b>	
3.1 Tahap-Tahap Prosedur Simulasi <i>Link Budget</i> Satelit Berstandar <i>Satellite Requirement L-Band</i>	9
3.1 Diagram Alur ( <i>Flowchart</i> ) Simulasi <i>Link Budget</i> Satelit Berstandar <i>Satellite Requirement L-Band</i>	18

## **BAB IV ANALISA SIMULASI *LINK BUDGET* SATELIT BERSTANDAR *SATELLITE***

### ***REQUIREMENT L-BAND***

4.1 Tampilan Awal	20
4.2 Tampilan Menu Utama	21
4.2.1 Perhitungan Gain Antena	22
4.2.1.1 Perhitungan Gain Antena Satelit	22
4.2.1.2 Perhitungan Gain Antena Stasiun Bumi	23
4.2.2 Perhitungan Gain to Noise Temperatur	24
4.2.2.1 Perhitungan Gain to Noise Temperatur (G/T) Satelit	24
4.2.2.2 Perhitungan Gain to Noise Temperatur (G/T) Stasiun Bumi	25
4.2.3 Perhitungan <i>Losses</i>	26
4.2.3.1 Perhitungan Free Space Loss (FSL) <i>Uplink</i>	26
4.2.3.2 Perhitungan Free Space Loss (FSL) <i>Downlink</i>	27
4.2.3.3 Perhitungan LTx	28
4.2.3.4 Perhitungan LRx	28
4.2.3.5 Perhitungan Total <i>Loss</i>	29
4.2.4 Perhitungan Daya Carrier to Noise Ratio	31
4.2.4.1 Perhitungan Daya Carrier to Noise Ratio (C/N) <i>Uplink</i>	31
4.2.4.2 Perhitungan Daya Carrier to Noise Ratio (C/N) <i>Downlink</i>	33
4.2.5 Perhitungan Daya Carrier to Noise Temperatur	34
4.2.5.1 Perhitungan Daya Carrier to Noise Temperatur (C/T) <i>Uplink</i>	34
4.2.5.2 Perhitungan Daya Carrier to Noise Temperatur (C/T) <i>Downlink</i>	36
4.2.6 Perhitungan <i>Link Budget</i> Satelit Berstandar <i>Satellite Requirement</i> L-Band	37
4.2.7 Perhitungan Grafik Perbandingan Frekuensi terhadap Gain	39
4.2.8 Perhitungan Grafik Perbandingan Frekuensi terhadap Gain to Noise Temperatur	40
4.2.9 Perhitungan Grafik Perbandingan Free Space Loss (FSL)	41
4.2.9.1 Perhitungan Grafik Perbandingan Frekuensi terhadap FSL	42
4.2.9.2 Perhitungan Grafik Perbandingan Jarak terhadap FSL	43
4.2.10 Perhitungan Grafik Perbandingan Frekuensi terhadap Pointing Error	44
4.2.11 Perhitungan Grafik Perbandingan Daya Carrier to Noise Ratio	45
4.2.11.1 Perhitungan Grafik Perbandingan Frekuensi terhadap Daya Carrier to Noise Ratio	46

4.2.11.2 Perhitungan Grafik Perbandingan Jarak terhadap Daya Carrier to Noise Ratio	47
4.2.12 Perhitungan Grafik Perbandingan Daya Carrier to Noise Temperatur	48
4.2.12.1 Perhitungan Grafik Perbandingan Frekuensi terhadap Daya Carrier to Noise Temperatur	49
4.2.12.2 Perhitungan Grafik Perbandingan Jarak terhadap Daya Carrier to Noise Temperatur	50
<b>BAB V PENUTUP</b>	
5.1 Kesimpulan	51
5.2 Saran	52
<b>DAFTAR PUSTAKA</b>	x
<b>LAMPIRAN 1</b>	xi