

DAFTAR PUSTAKA

- [1] F. M. Wu *et al.*, “Performance comparison of OFDM signal and CAP signal over high capacity RGB-LED-based WDM visible light communication,” *IEEE Photonics J.*, vol. 5, no. 4, 2013, doi: 10.1109/JPHOT.2013.2271637.
- [2] S. Long, M. A. Khalighi, M. Wolf, Z. Ghassemlooy, and S. Bourennane, “Performance of carrier-less amplitude and phase modulation with frequency domain equalization for indoor visible light communications,” *2015 4th Int. Work. Opt. Wirel. Commun. IWOW 2015*, no. July 2020, pp. 16–20, 2015, doi: 10.1109/IWOW.2015.7342257.
- [3] Y. Chen, Z. Li, P. Liu, and S. Liu, “The BER performance comparison of MSK and GMSK schemes for short-range visible light communication,” in *2017 9th IEEE International Conference on Communication Software and Networks, ICCSN 2017*, Dec. 2017, vol. 2017-January, pp. 611–614, doi: 10.1109/ICCSN.2017.8230184.
- [4] J. Rodríguez, D. G. Lamar, D. G. Aller, P. F. Miaja, and J. Sebastián, “Efficient visible light communication transmitters based on switching-mode dc-dc converters,” *Sensors (Switzerland)*, vol. 18, no. 4, pp. 1–18, 2018, doi: 10.3390/s18041127.
- [5] A. A. Kusuma, “Implementasi Digital Subscriber Line Access Multiplekser (DSLAM) pada teknologi Very High Data Rate Digital Subscriber Line (VDSL),” pp. 1–6.
- [6] N. M. Ridzuan, M. F. L. Abdullah, M. B. Othman, and M. B. Jaafar, “A Carrierless Amplitude Phase (CAP) modulation format: Perspective and prospect in optical transmission system,” *Int. J. Electr. Comput. Eng.*, vol. 8, no. 1, pp. 585–595, 2018, doi: 10.11591/ijece.v8i1.pp585-595.
- [7] K. O. Akande, P. A. Haigh, and W. O. Popoola, “On the Implementation of Carrierless Amplitude and Phase Modulation in Visible Light Communication,” *IEEE Access*, vol. 6, pp. 60532–60546, 2018, doi: 10.1109/ACCESS.2018.2876001.

- [8] K. Nizam, “Analisa Kinerja Modulasi Gaussian Minimum Shift Keying,” 2010.
- [9] “MSK transmitter and receiver.” <http://www.dsblog.com/2009/06/16/msk-transmitter-receiver/> (accessed Dec. 18, 2020).
- [10] M. D. McKinley, K. A. Remley, M. Myslinski, J. S. Kenney, D. Schreurs, and B. Nauwelaers, “EVM calculation for broadband modulated signals,” *64th ARFTG Microw. Meas. Conf. Digit. Commun. Syst. Metrics, ARFTG 2004*, pp. 45–52, 2004.
- [11] E. P. Wisnu, W. I. M. P. Adi, and D. S. M. K. Fadilla, “Multipath fading, Jaringan CDMA, EV-DO Rev. A.,” *Pengaruh Multipath Fading Terhadap Performansi Pada Downlink Jar. Cdma2000 IX Ev-Do Revis. a*, pp. 1–8, 2014.