

DAFTAR PUSTAKA

- [1] A. Ghosh, “Possibilities and challenges for the inclusion of the electric vehicle (EV) to reduce the carbon footprint in the transport sector: A review,” *Energies*, vol. 13, no. 10, 2020, doi: 10.3390/en13102602.
- [2] F. Cadini, C. Sbarufatti, F. Cancelliere, and M. Giglio, “State-of-life prognosis and diagnosis of lithium-ion batteries by data-driven particle filters,” *Appl. Energy*, vol. 235, no. June 2018, pp. 661–672, 2019, doi: 10.1016/j.apenergy.2018.10.095.
- [3] I. Baccouche, S. Jemmali, A. Mlayah, B. Manai, and N. E. Ben Amara, “Implementation of an improved Coulomb-counting algorithm based on a piecewise SOC-OCV relationship for SOC estimation of Li-ion battery,” *Int. J. Renew. Energy Res.*, vol. 8, no. 1, pp. 178–187, 2018, doi: 10.20508/ijrer.v8i1.6686.g7292.
- [4] A. Mariani, T. Stockley, and K. Thanapalan, “Simple and Effective OCV Prediction Mechanism for VRLA Battery Systems,” *Avestia.Com*, no. 140, pp. 1–10, 2014, [Online]. Available: http://avestia.com/ICMEM2014_Proceedings/papers/140.pdf
- [5] C. Vidal, P. Malysz, P. Kollmeyer, and A. Emadi, “Machine Learning Applied to Electrified Vehicle Battery State of Charge and State of Health Estimation: State-of-the-Art,” *IEEE Access*, vol. 8, pp. 52796–52814, 2020, doi: 10.1109/ACCESS.2020.2980961.
- [6] Vehicular Technology Society and Institute of Electrical and Electronics Engineers, “2015 IEEE Vehicle Power and Propulsion Conference (VPPC): proceedings: 19-22 October 2015, Montreal, Quebec,” pp. 1–6, 2015.
- [7] M. Zhang, K. Wang, and Y. T. Zhou, “Online state of charge estimation of lithium-ion cells using particle filter-based hybrid filtering approach,” *Complexity*, vol. 2020, 2020, doi: 10.1155/2020/8231243.
- [8] I. Baccouche, A. Mlayah, S. Jemmali, B. Manai, and N. E. Ben Amara, “Implementation of a Coulomb counting algorithm for SOC estimation of Li-Ion battery for multimedia applications,” *12th Int. Multi-Conference Syst. Signals Devices, SSD 2015*, pp. 1–6, 2015, doi: 10.1109/SSD.2015.7348255.
- [9] J. P. Rivera-Barrera, N. Muñoz-Galeano, and H. O. Sarmiento-Maldonado, *Soc estimation for lithium-ion batteries: Review and future challenges*, vol. 6, no. 4. 2017. doi: 10.3390/electronics6040102.
- [10] J. Loukil, F. Masmoudi, and N. Derbel, “State of charge estimation of lead acid battery using a Kalman filter,” *2017 14th Int. Multi-Conference Syst. Signals Devices, SSD 2017*, vol. 2017-January, pp. 308–312, 2017, doi: 10.1109/SSD.2017.8167026.

- [11] McRoberts, Michael. *Beginning Arduino*. Apress, 2013, doi : 10.1007/978-1-4302-5017-3, vol. 1999, no. December, pp. 1–6, 2006.
- [12] N. Ratnawati and S. Sunardi, “Load Characteristics with Current Detection Using an Arduino Based ACS712 Sensor,” *Bul. Ilm. Sarj. Tek. Elektro*, vol. 2, no. 2, p. 83, 2020, doi: 10.12928/biste.v2i2.1522.
- [13] M. H. Meinanda, M. Annisa, N. Muhandri, and dan K. Suryadi, “Prediksi masa studi sarjana dengan artificial neural network,” *Internetworking Indones. J.*, vol. 1, no. 2, pp. 31–35, 2009.