

# CONTENTS

## Agreement Page

## Originality Statements

<b>ABSTRACT</b>	<b>iv</b>
<b>PREFACE</b>	<b>v</b>
<b>Contents</b>	<b>viii</b>
<b>List of Figures</b>	<b>x</b>
<b>List of Tables</b>	<b>xi</b>
<b>1 INTRODUCTION</b>	<b>1</b>
1.1 Background . . . . .	1
1.2 Problem Formulation . . . . .	3
1.3 Objectives . . . . .	3
1.4 Scope of Works . . . . .	3
1.5 Research Method . . . . .	4
1.6 Undergraduate Thesis Organization . . . . .	4
<b>2 BASIC CONCEPT</b>	<b>5</b>
2.1 Tranport Layer . . . . .	5
2.1.1 Transmission Control Protocol (TCP) . . . . .	5
2.1.2 User Datagram Protocol (UDP) . . . . .	6
2.2 Raspberry Pi . . . . .	6
2.3 Client and Attacker Devices . . . . .	7
2.4 Denial of Service (DoS) Attack . . . . .	7
2.4.1 SYN Flood Attack . . . . .	8
2.4.2 UDP Flood Attack . . . . .	9
2.5 Host Intrusion Prevention System (HIPS) . . . . .	10
2.6 Snort . . . . .	10
2.7 RaspAP . . . . .	11
2.8 Hping3 . . . . .	11

<b>3 SYSTEM PLANNING</b>	<b>12</b>
3.1 System Design . . . . .	12
3.1.1 System Description . . . . .	13
3.1.2 System Requirement . . . . .	13
3.2 Raspberry Pi Configuration . . . . .	14
3.2.1 Raspberry Pi as A Router Configuration . . . . .	15
3.2.2 Snort Configuration . . . . .	15
3.3 Virtual Machines (VM) installation on VirtualBox . . . . .	17
3.4 Server's VM Configuration . . . . .	17
3.5 Client's VM Configuration . . . . .	18
3.6 Research Scenarios . . . . .	19
3.6.1 Total Incoming Packets Testing . . . . .	19
3.6.2 Using Snort Testing . . . . .	19
3.7 CPU and Memory Usage Testing . . . . .	19
<b>4 PERFORMANCE EVALUATION</b>	<b>21</b>
4.1 Total Incoming Packets . . . . .	21
4.1.1 Client's Connection . . . . .	21
4.1.2 Total Incoming Packets from Attackers Testing . . . . .	22
4.2 Using Snort Testing . . . . .	23
4.2.1 Active Snort Impact for Client Connection . . . . .	23
4.2.2 Total Packet Processed by HIPS Snort . . . . .	24
4.3 CPU and Memory Usage Testing . . . . .	26
<b>5 CONCLUSIONS</b>	<b>27</b>
5.1 Conclusion . . . . .	27
5.2 Suggestion . . . . .	28
<b>Bibliography</b>	<b>29</b>