

## LIST OF FIGURES

Figure 2.1 Absorber design diagram.....	5
Figure 2.2 Absorber as an anti-radar coating material.....	6
Figure 2.3 Impedance difference between two medium causes wave reflection.....	7
Figure 2.4 Impedance adjustment circuit.....	7
Figure 2.5 Impedance adjustment circuit model of the absorber.....	8
Figure 3.1 Research flowchart.....	12
Figure 3.2 (a) Square absorber, based on the approach with AMC resonant frequency equation, and (b) SRR absorber.....	14
Figure 3.3 One absorber cell with double resonance.....	15
Figure 3.4 Boundary configuration in the simulation.....	16
Figure 3.5 Dimension Variables of one absorber cell.....	17
Figure 3.6 Optimization scheme.....	18
Figure 4.1 Absorber A, absorber B, absorber C, and checkerboard pattern.....	18
Figure 4.2 Simulation result for Absorber A, B, and C.....	19
Figure 4.3 Simulation result for absorber A, B, and A-B.....	20
Figure 4.4 Simulation result for Absorber A, C, and A-C.....	21
Figure 4.5 Simulation result for Absorber B, C, and B-C.....	21
Figure 4.6 Simulation of one absorber cell with varying incident wave polarization. .....	22
Figure 4.7 Simulation of checkerboard pattern absorber with varying incident wave polarization.....	22
Figure 4.8 Modified absorber SRR pattern.....	23
Figure 4.9 Simulation of modified SRR pattern absorber.....	23
Figure 4.10 Absorber A, absorber B, and A-B combination.....	24
Figure 4.11 Simulation results of absorber A, absorber B, and A-B combination.....	24
Figure 4.12 Simulation results of absorber A-B toward variations in incident wave polarization.....	25
Figure 4.13 Polyimide absorber design simulation.....	26
Figure 4.14 Absorptivity rate.....	26
Figure 4.15 Reflection coefficient for a thickness of 0.3 mm toward the polarization angle of the incident wave.....	27

Figure 4.16 Reflection coefficient for a thickness of 0.4 mm toward the polarization angle of the incident wave. ....	28
Figure 4.17 Reflection coefficient for a thickness of 0.5 mm toward the polarization angle of the incident wave. ....	29
Figure 4.18 Reflection coefficient for a thickness of 0.6 mm toward the polarization angle of the incident wave. ....	29
Figure 4.19 Reflection coefficient for the absorber A and B in area difference (delta area) of $0.8 \text{ mm}^2$ toward the polarization angle of the incident wave. ..	31
Figure 4.20 Reflection coefficient for the absorber A and B in area difference (delta area) of $1.2 \text{ mm}^2$ toward the polarization angle of the incident wave. ..	31
Figure 4.21 Reflection coefficient for the absorber A and B in area difference (delta area) of $3.4 \text{ mm}^2$ toward the polarization angle of the incident wave. ..	32
Figure 4.22 Reflection coefficient for the absorber A and B in area difference (delta area) of $4.3 \text{ mm}^2$ toward the polarization angle of the incident wave. ..	33