

## REFERENCES

- [1] M. F. Iskander, Electromagnetic fields, and waves. Waveland Press, 2000.
- [2] B. Wang, X. Zhaia, G. Wang, W. Huang, dan L. Wang., “A novel dual-band terahertz metamaterial absorber for a sensor application A novel dual-band terahertz metamaterial absorber for a sensor application,” Journal of Applied Physics, vol. 117 (1), 2015.
- [3] M. S. Sim, K. Y. You, F. B. Esa dan Y. L. Chan, ”Broadband metamaterial microwave absorber for X-Ku band using planar split ring-slot structures,” 2017 Progress in Electromagnetics Research Symposium - Fall (PIERS - FALL), Singapore, 2017, hal. 215-221.
- [4] E. Ameri, S. H. Esmaeli, dan S. H. Sedighy, “Ultra-wide band radar cross section reduction using multilayer artificial magnetic conductor metasurface,” J. Phys. D. Appl. Phys., vol. 51, no. 28, hal. 285-304, 2018.
- [5] J. B. Pendry, A. J. Holden, D. J. Robbins and W. J. Stewart, ”Magnetism from conductors and enhanced nonlinear phenomena,” IEEE Transactions on Microwave Theory and Techniques, vol. 47, no. 11, hal. 2075-2084, Nov. 1999.
- [6] Marqués, R., Martin, F. dan Sorolla, M., Metamaterials with negative parameters: theory, design, and microwave applications. Hoboken, NJ : John Wiley & Sons, Inc., 2007.
- [7] Wang, B.X., Zhu, H.X. dan Huang, W.Q., “Multiple-Band Ultra-Thin Perfect Metamaterial Absorber Using Analogy Split-Ring Resonators,” Plasmonics, hal. 1-12, 2019.
- [8] B. Syihabuddin, A. H. Gunawan, M. R. Effendi dan A. Munir, ”Study on Multilayer EM Wave Absorber Composed of Metasurface for X-band Application,” 2019 IEEE International Conference on Communication, Networks and Satellite (Comnetsat), Makassar, Indonesia, 2019, hal. 14-17.
- [9] Sen, G., Ghosh, A., Kumar, M., Islam, S.N. dan Das, S., “A Co-Polarized Microwave Absorber with Dual Mode Resonance Based on Dual Split Ring Geometry for Wi-Max and WLAN Applications,”. Progress In Electromagnetics Research, 86, hal. 145-152, 2019.
- [10] H. B. Baskey dan M. J. Akhtar, "A dual-band hexagonal ring based

- polarization-insensitive metamaterial absorber," IEEE MTT-S International Microwave and RF Conference, New Delhi, 2013, hal. 1-4.
- [11] T. T. Nguyen and S. Lim, "Bandwidth enhancement of metamaterial absorber using *double resonance*," 2017 IEEE Asia Pacific Microwave Conference (APMC), Kuala Lumpur, 2017, pp. 380-382.
  - [12] I. Fikry, L. O. Nur, B. S. Nugroho and A. Munir, "Thin EM Wave Absorber Metasurface Based on Artificial Magnetic Conductor," 2018 Progress in Electromagnetics Research Symposium (PIERS-Toyama), Toyama, 2018, pp. 1100-1103.
  - [13] R. A. Mulyadi, L. O. Nur, and B. Syihabuddin, "Investigation of Checkerboard Pattern for EM Wave Absorber using Broadside SRR," 2020 IEEE International Conference on Communication, Networks and Satellite (Commetsat), 2020, pp. 277-281.
  - [14] L. O. Nur, A. Kurniawan, Sugihartono dan A. Munir, "Theoretical Analysis of Resonant Frequency for AMC-based Absorber Composed of Square Patch Array," International Journal on Electrical Engineering and Informatics, vol. 7, no. 2, hal. 284-296, 2015.
  - [15] E. Ameri, S. H. Esmaeli, dan S. H. Sedighy, "Ultra-wide band radar cross section reduction using multilayer artificial magnetic conductor metasurface," J. Phys. D. Appl. Phys., vol. 51, no. 28, hal. 285-304, 2018.
  - [16] M. Li, H.-L. Yang, X.-W. Hou, Y. Tian, and D.-Y. Hou, "Perfect metamaterial absorber with dual bands," Progress in Electromagnetics Research, Vol. 108, 37-49, 2010.
  - [17] M. Yoo and S. Lim, "Polarization-Independent and Ultrawideband Metamaterial Absorber Using a Hexagonal Artificial Impedance Surface and a Resistor-Capacitor Layer," in IEEE Transactions on Antennas and Propagation, vol. 62, no. 5, pp. 2652-2658, 2014.
  - [18] D. Sievenpiper. "High-impedance electromagnetic surfaces", PhD Thesis, UCLA, 1999.
  - [19] N. Engheta dan R. W. Ziolkowski, Electromagnetic Metamaterials: Physics and Engineering Explorations, 1st Edition, New Jersey: Wiley- IEEE Press, 2006.
  - [20] Nur, Levy Olivia et al. Perancangan dan Fabrikasi Penyerap Gelombang Elektromagnetik Patch Segi Enam Berbasis Surface Textured. Teknika - Jurnal

Penelitian dan Pengembangan Telekomunikasi, Kendali, Komputer, Elektrik, dan Elektronika, vol. 1, no.1, 2016.

- [21] Munir Achmad, April 2011, "Hybrid De-embedding Technique for Microwave Absorber Characterization", Telkomnika, vol. 9, no. 1.
- [22] F. -Y. Kuo and R. -B. Hwang, "High-Isolation X-Band Marine Radar Antenna Design," in IEEE Transactions on Antennas and Propagation, vol. 62, no. 5, pp. 2331-2337, May 2014, doi: 10.1109/TAP.2014.2307296.
- [23] Chan, Y.K., Koo, V.C. and Lim, T.S., 2007. Conceptual design of a high resolution, low cost X-band airborne synthetic aperture radar system. PIERS Online, 3(6), pp.943-947.