

LIST OF FIGURE

Figure 2.1 FMCW radar vital signs detection diagram.....	6
Figure 2.2 FMCW Radar Waveform	7
Figure 2.3 The line of radiators (broadside) if all antenna elements are fed in phase	8
Figure 2.4 Phased array antenna principle	9
Figure 2.5 Components of the Butler Matrix.....	11
Figure 2.6 Symbol for directional couplers	12
Figure 2.7 SIW Parameters	14
Figure 2.8 (a) Waveguide dielectric. (b) Rectangular Waveguide.....	15
Figure 3.1 Illustrations of multi-target detection	19
Figure 3.2 Proposed Method.....	20
Figure 3.3 Proposed research of SIW Beamforming	21
Figure 3.4 Butler Matrix Output Phase	22
Figure 3.5 Basic parameters of SIW Transmission	24
Figure 4.1 Scheme of Designing and Simulating SIW Parameters	26
Figure 4.2 BM Simulation Diagram	26
Figure 4.3 Diagram of the testing and data collection process	27
Figure 4.4 Prototype measurement (a) Illustration of BM measurements using VNA. (b) Documentation of the measurements	28
Figure 4.5 (a) Illustration Butler Matrix Horizontal radiation pattern testing process in the laboratory. (b) Documentation of the experiment Butler matrix H-Plane radiation pattern measurement configuration	29
Figure 4.6 Integration of FMCW radar devices with Butler matrix	30
Figure 4.7 Prototype beamforming with SIW techniques on FMCW radar. (a) Parts of beamforming FMCW Radar. (b) Integration of Butler Matrix	31
Figure 4.8 The experiment of Beamforming target detection. (a) Illustration of the experimental setup side view. (b) Illustration of radar position setup. (c) Documentation of the experiment.....	33

Figure 4.9 Breath detection testing using FMCW radar	33
Figure 4.10 The experiment of multi-target detection. (a) Illustration of the experimental In the first scenario. (b) Illustration of the second scenario.....	34
Figure 4.11 Documentation of the experiment in the first scenario.....	35
Figure 4.12 Documentation of the experiment in the second scenario	36
Figure 5.1 Results of radiation 4 element antenna	38
Figure 5.2 Structure of Antenna Array	39
Figure 5.3 Results of 3D radiation pattern antenna with phase differences.....	39
Figure 5.4 S-parameters of the SIW transmission line design	41
Figure 5.5 Phase of the SIW transmission line design.....	41
Figure 5.6 Results of E-fields distribution at frequency 24GHz.....	41
Figure 5.7 Proposed analysis scheme for each component.....	42
Figure 5.8 Proposed 90° HC structure in SIW.....	43
Figure 5.9 (a) Simulation results of S_{11} , S_{21} , S_{51} , S_{61} , S_{33} , S_{43} , S_{73} , and S_{83} . (b) Simulation results of phase differences between output ports and results phase output ports	44
Figure 5.10 E-Field distribution of hybrid coupler feed by port 1 and port 3	45
Figure 5.11 Proposed -45° phase shifter and crossover structure in SIW.....	45
Figure 5.12 Simulated S-parameters and phase of crossover	46
Figure 5.13 Simulated S-parameters and phase of -45° phase shifter	47
Figure 5.14 E-Field distribution of phase shifter -45° and crossover. (a) With input port 1 and port 2. (b) With input port 1 and port 3	47
Figure 5.15 Proposed 0° phase shifter and crossover structure in SIW	48
Figure 5.16 Simulated S-parameters and phase of 0° phase shifter.....	49
Figure 5.17 Simulated S-parameters and phase of crossover	49
Figure 5.18 E-Field distribution of 0° phase shifter and crossover (a) With input port 1 and port 2. (b) With input port 1 and port 3.....	50
Figure 5.19 A combination of a 90° hybrid coupler with a -45° phase shifter and a crossover on the SIW transmission line.....	51
Figure 5.20 Simulated S-parameters port 1, port 2, port 3, and port 4 of 90° hybrid coupler, -45° phase shifter, and crossover	51
Figure 5.21 Results of E-fields distribution at the second part	52
Figure 5.22 Results of Phase.....	52
Figure 5.23 A combination of parts 1, 2, and 3 on the SIW transmission line	53

Figure 5.24 Simulated S-parameters port 1, port 2, port 3, and port 4 of 90° hybrid coupler, -45° phase shifter, and crossover	53
Figure 5.25 Results of E-fields distribution in the third part	54
Figure 5.26 The output phase result of combining 3 parts.....	54
Figure 5.27 Design of SIW 4 x 4 Butler Matrix	55
Figure 5.28 Simulated S-parameters 4 x 4 Butler Matrix	55
Figure 5.29 Results of E-fields distribution in 4 x 4 Butler Matrix	56
Figure 5.30 Results of phase 4 x 4 Butler Matrix	56
Figure 5.31 Design transition input port	58
Figure 5.32 Simulated S-parameters transition input port	58
Figure 5.33 Design of SIW 4 x 4 Butler Matrix with transition input port	59
Figure 5.34 Simulated S-parameters 4 x 4 Butler Matrix with transition input port .	59
Figure 5.35 Results of phase 4 x 4 Butler Matrix with transition input port	60
Figure 5.36 S-parameters results from measuring and simulation of the Butler Matrix	61
Figure 5.37 (a) Design of 24 GHz Series Fed Microstrip Patch Antenna Array. (b) Fabricated Antenna	61
Figure 5.38 (a) Simulated and measured reflection coefficients of the antenna. (b) VSWR of the antenna	62
Figure 5.39 Beam direction from simulation and measurement results of the antenna at 24GHz.....	63
Figure 5.40 Design of Beamforming with Antenna.....	64
Figure 5.41 Simulated isolation loss and reflection coefficients of the antenna.....	65
Figure 5.42 Simulated Radiation pattern of the BM	65
Figure 5.43 Comparison of antenna array radiation patterns with BM.....	66
Figure 5.44 Measurement isolation loss and return loss of the antenna.	67
Figure 5.45 Results from measuring and simulation the radiation pattern of the Butler Matrix	67
Figure 5.46 H-Plane Port 1 and Port 2 Beam direction from simulation and measurement results from BM.....	68
Figure 5.47 H-Plane Port 3 and Port 4 Beam direction from simulation and measurement results from BM.....	69
Figure 5.48 Magnitude response of output FMCW radar	72
Figure 5.49 Magnitude response of output in the frequency domain.	73

Figure 5.50 Time domain representation of phase detector output in ROI.....	73
Figure 5.51 Small displacement of phase detector output in ROI	74
Figure 5.52 Phase response radar without a target on port 1	75
Figure 5.53 Magnitude response when target position is at -40° and 40°	76
Figure 5.54 Phase response at port 2 with target position -40°	76
Figure 5.55 Comparison of phase response at port 2 between target position -40° and target position 40°	77
Figure 5.56 Phase response at port 3 with target position 40°	77
Figure 5.57 Comparison of phase response at port 3 between target position 40° and target position -40°	78
Figure 5.58 Phase response at port 1 with target position 15°	79
Figure 5.59 Comparison of phase response at port 1 between target position 15° and target position -15°	79
Figure 5.60 Phase response at port 4 with target position -15°	80
Figure 5.61 Comparison of phase response at port 4 between target position 15° and target position -15°	80
Figure 5.62 Phase response multi-target radar on port 1	81
Figure 5.63 Phase response multi-target radar on port 2	82
Figure 5.64 Phase response multi-target radar on port 3	82
Figure 5.65 Phase response multi-target radar on port 4	83
Appendix A.1 Phase response without a target on port 1	90
Appendix A.2 Phase response without a target on port 2	90
Appendix A.3 Phase response without a target on port 3	91
Appendix A.4 Phase response without a target on port 4	91
Appendix B.1 Measurement Tx Antenna.....	92
Appendix B.2 Laboratory Setup measuring Tx Antenna.....	92
Appendix C.1 Laboratory Setup measuring Butler Matrix.....	93
Appendix C.2 Measurement S-parameters Port 1 to Port 2 Butler Matrix	93
Appendix C.3 Measurement S-parameters Port 1 to Port 3 Butler Matrix	94
Appendix C.4 Measurement S-parameters Port 3 to Port 4 Butler Matrix	94
Appendix C.5 Measurement S-parameters Port 2 to Port 4 Butler Matrix	95
Appendix D.1 Laboratory Setup measuring Butler Matrix with Antenna.....	96
Appendix D.2 Measurement port 1 Butler matrix	96
Appendix D.3 Measurement port 2 Butler matrix	97

Appendix D.4 Measurement port 3 Butler matrix	97
Appendix D.5 Measurement port 4 Butler matrix	98
Appendix E.1 Anritsu MS46322A Vector Network Analyzer Series up to 43.5 GHz.....	99
Appendix E.2 Signal Analyzer KEYSIGHT N9020A MXA, 10 Hz to 26.5 GHz	99
Appendix E.3 KEYSIGHT MXG Analog signal generator N5183B, 9 kHz - 40 GHz.....	100
Appendix E.4 WR-34 Waveguide Standard Horn Antenna 22 GHz to 33 GHz	100