

DAFTAR SINGKATAN

| | |
|------------------|---|
| ESP32 | : <i>Espressif System Platform 32</i> |
| TDS | : <i>Total Dissolved Solids</i> |
| PPM | : <i>Part Per Million</i> |
| CM | : <i>Senti Meter</i> |
| dBm | : <i>Decibel Milliwatt</i> |
| EC | : <i>Electrial Conductivity</i> |
| AI | : <i>Artificial Intelligence</i> |
| DC | : <i>Direct Current</i> |
| LCD | : <i>Liquid Crystal Display</i> |
| IDE | : <i>Integrated Development Environment</i> |
| PCB | : <i>Printed Circuit Board</i> |
| U | : <i>Universal</i> |
| COA | : <i>Center of Area</i> |
| DC | : <i>Direct Current</i> |
| mA | : <i>Miliampere</i> |
| V | : <i>Volt</i> |
| M | : <i>Meter</i> |
| mm | : <i>Milimeter</i> |
| g | : <i>Gram</i> |
| Kgf | : <i>Gaya Kilogram</i> |
| I ² C | : <i>Inter-Integrated Circuit</i> |
| SCL | : <i>Serial Clock</i> |
| SDA | : <i>Serial Data Informasi</i> |
| MB | : <i>Megabyte</i> |
| KB | : <i>Kilobyte</i> |
| MHz | : <i>Megahertz</i> |
| A | : <i>Ampere</i> |