

DAFTAR SINGKATAN

| | |
|---------------|---|
| SPC | : <i>Single Parity Check</i> |
| SPC-NC | : <i>Single Parity Check network coding</i> |
| MAC | : <i>Multiple Access Channel</i> |
| ISM | : <i>Iterative Spatial Demapping</i> |
| BER | : <i>Bit Error Rate</i> |
| SNR | : <i>Signal to Noise Ratio</i> |
| VN | : <i>Variable Nodes</i> |
| CN | : <i>Check Nodes</i> |
| BPSK | : <i>Binary-phase Shift Keying</i> |
| LLR | : <i>Log-likelihood Ratio</i> |
| DF | : <i>Decode-and-Forward</i> |
| AF | : <i>Amplify-and-Forward</i> |
| RS | : <i>Relay Station</i> |
| S-D | : <i>Source-to-Destination</i> |
| S-R | : <i>Source-to-Relay</i> |
| R-D | : <i>Relay-to-Destination</i> |
| MIMO | : <i>multiple-input multiple-output</i> |
| SPA | : <i>Sum Product Algorithm</i> |
| IoT | : <i>Internet of Things</i> |
| TDMA | : <i>Time Division Multiplex Access</i> |
| XOR | : <i>Exclusive OR</i> |
| EXIT | : <i>Extrinsic Information Transfer</i> |