Daftar Pustaka

[1]   N. A. Mohidem, N. Hashim, R. Shamsudin, and H. C. Man, "Rice for food security: revisiting its production, diversity, rice milling process and nutrient content," Agriculture (Switzerland), vol. 12, no. 6. MDPI, Jun. 01, 2022. doi: 10.3390/agriculture12060741.

[2]   N. H. Ab Samat, A. R. Saili, Z. Yusop, F. Abdul Fatah, and A. S. A. Aziz, "Factors affecting selection of rice among the consumer in Shah Alam, Selangor," in IOP Conference Series: Earth and Environmental Science, Institute of Physics, 2022. doi: 10.1088/1755-1315/1059/1/012005.

[3]   P. Wasan, S. Kumar, N. Saini, S. Shankar Bhatt, A. Bhatt, and J. Ballabh, "Review on nutritional content of various types of rice," Journal of Food Research and Nutrition, vol. 1, no. 1, pp. 1–10, 2022.

[4]   H. Chen, G. Zhou, W. He, X. Duan, and H. Jiang, "Classification and identification of agricultural products based on improved MobileNetV2," Sci Rep, vol. 14, no. 1, Dec. 2024, doi: 10.1038/s41598-024-53349-w.

[5]   T. Li et al., "The image-based analysis and classification of urine sediments using a LeNet-5 neural network," Comput Methods Biomech Biomed Eng Imaging Vis, vol. 8, no. 1, pp. 109–114, Jan. 2020, doi: 10.1080/21681163.2019.1608307.

[6]   O. I. Berngardt, "Improving classification neural networks by using absolute activation function (MNIST/LeNET-5 example)," Apr. 2023, [Online]. Available: http://arxiv.org/abs/2304.11758

[7]   A. Zaibi, A. Ladgham, and A. Sakly, "A lightweight model for traffic sign classification based on enhanced LeNet-5 network," J Sens, vol. 2021, 2021, doi: 10.1155/2021/8870529.

[8]   S. Qadri et al., "A machine vision approach for classification the rice varieties using statistical features," Int J Food Prop, vol. 24, no. 1, pp. 1615–1630, 2021, doi: 10.1080/10942912.2021.1986523.

[9]   T. Nga et al., "Extending color properties for texture descriptor based on local ternary patterns to classify rice varieties," EAI Endorsed Transactions on Industrial Networks and Intelligent Systems, p. 173605, Jul. 2018, doi: 10.4108/eai.7-3-2022.173605.

[10]   T. T. K. Nga, T. V. Pham, D. M. Tam, I. Koo, V. Y. Mariano, and T. Do-Hong, "Combining binary particle swarm optimization with support vector machine for enhancing rice varieties classification accuracy," IEEE Access, vol. 9, pp. 66062–66078, 2021, doi: 10.1109/ACCESS.2021.3076130.

[11]   Y. Lecun et al., "Comparison of learning algorithms for handwritten digit recognition," 1995.

[12]   M. Tasci, A. Istanbullu, S. Kosunalp, T. Iliev, I. Stoyanov, and I. Beloev, "An efficient classification of rice variety with quantized neural networks," Electronics (Switzerland), vol. 12, no. 10, May 2023, doi: 10.3390/electronics12102285.

[13]   S. Han, J. Pool, J. Tran, and W. J. Dally, "Learning both weights and connections for efficient neural networks," in Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 1, in NIPS'15. Cambridge, MA, USA: MIT Press, 2015, pp. 1135–1143.

[14]   M. M. Islam, G. M. S. Himel, Md. G. Moazzam, and M. S. Uddin, "Aruzz: An image dataset of rice varieties," V2, 2023

[15]   K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition," ICLR, Sep. 2014, [Online]. Available: http://arxiv.org/abs/1409.1556