

DAFTAR SINGKATAN

ADC	= <i>Analog-to-Digital Converter</i>
BNC	= <i>Bayonet Neill-Concelman</i>
Bps	= <i>Bit per second</i>
CSV	= <i>Comma-Separated Values</i>
DAC	= <i>Digital to Analog Converter</i>
DO	= <i>Dissolved Oxygen</i>
EAS	= <i>Emergency Alert System</i>
F.S.	= <i>Full Scale</i>
FAQ	= <i>Frequently Asked Question</i>
Gbps	= <i>GigaBytes per Second</i>
GHz	= <i>Gigahertz</i>
GPIO	= <i>General Purpose Input/Output</i>
IMNV	= <i>Infectious myonecrosis virus</i>
IoT	= <i>Internet of Things</i>
JSON	= <i>JavaScript Object Notation</i>
Kbps	= <i>Kilo bit per second</i>
KKP	= <i>Kementerian Kelautan dan Perikanan</i>
LCD	= <i>Liquid Crystal Display</i>
Mbps	= <i>Megabit per second</i>
Ms	= <i>Miliseconds</i>
MWA	= <i>Monitoring Warning Action</i>
NaOH	= <i>Natrium Hidroksida</i>
NoSQL	= <i>Not only SQL</i>
PCB	= <i>Printed Circuit Board</i>

pH	= <i>Potential of Hydrogen</i>
Ppm	= <i>Part Per Million</i>
PWM	= <i>Pulse Width Modulation</i>
QoS	= <i>Quality of Service</i>
RAS	= <i>Recirculating Aquaculture System</i>
RTDB	= <i>Realtime Database</i>
SoC	= <i>System on Chip</i>
SPI	= <i>Serial Peripheral Interface</i>
SRAM	= <i>Static Random Access Memory</i>
TDS	= <i>Total Dissolved Solid</i>
TSV	= <i>Taura Syndrome Virus</i>
UART	= <i>Universal Asynchronous Receiver-Transmitter</i>
UI	= <i>User Interface</i>
URL	= <i>Uniform Resource Locator</i>
Wi-Fi	= <i>Wireless Fidelity</i>
WLAN	= <i>Wireless Local Area Network</i>
WSSV	= <i>White Spot Syndrome Virus</i>