ABSTRACT

Optical Distribution Cabinet (ODC) is a crucial component in an optical network

system that acts as a distribution point for fiber optic cables from the center to the customer.

However, the placement of conventional ODCs on the ground has a number of drawbacks, such

as vulnerability to vandalism, environmental damage, space limitations, and aesthetic and

regulatory issues in urban areas. The main issue raised in this research is the weak security and

efficiency aspects of conventional ODCs, which impact the reliability of Fiber to The Home

(FTTH) services.

As a solution, a prototype underground ODC equipped with an RFID-based automatic

lock system and a hydraulic actuator mechanism to automatically open the cabinet cover was

designed. This design aims to improve physical security and technician accessibility, while

maintaining space efficiency and environmental aesthetics. The system uses an Arduino

microcontroller, RFID reader, LED and buzzer indicators, and hydraulic actuators customized

for the prototype's needs. The system installation is done inside a wooden manhole that

simulates the installation conditions below ground level.

The test results show that the ODC prototype system works optimally and is feasible to

develop. The initial physical design used the existing prototype dimensions of $48.5 \text{ cm} \times 40.5$

cm × 14 cm as a reference for performance evaluation. The security system was enhanced

through the integration of microcontroller-based RFID and solenoid, which successfully

authenticated 100% of valid cards and rejected all unregistered cards. LED indicators and

buzzers provide immediate feedback, enhancing access security. The use of hydraulic actuators

enables automatic opening of the ODC lid to 90° within 3 seconds, supporting the work

efficiency of technicians in the field. Thus, this prototype ODC is considered feasible as a safer

and more efficient alternative to conventional ODCs.

Keywords: Arduino, Hydraulics, Security, Optical Distribution Cabinet, RFID

vi