

## DAFTAR PUSTAKA

- [1] M. Sheng *et al.*, “On-demand : Achieving QoS differentiation for D2D communications,” *IEEE Commun. Mag.*, vol. 53, no. 7, pp. 162–170, 2015, doi: 10.1109/MCOM.2015.7158280.
- [2] A. Asadi, Q. Wang, and V. Mancuso, “A survey on device-to-device communication in cellular networks,” *IEEE Commun. Surv. Tutorials*, vol. 16, no. 4, pp. 1801–1819, 2014, doi: 10.1109/COMST.2014.2319555.
- [3] D. Feng, L. Lu, Y. W. Yi, G. Y. Li, G. Feng, and S. Li, “Device-to-device communications underlaying cellular networks,” *IEEE Trans. Commun.*, vol. 61, no. 8, pp. 3541–3551, 2013, doi: 10.1109/TCOMM.2013.071013.120787.
- [4] J. Liu, M. Sheng, L. Liu, Y. Shi, and J. Li, “Modeling and Analysis of SCMA Enhanced D2D and Cellular Hybrid Network,” *IEEE Trans. Commun.*, vol. 65, no. 1, pp. 173–185, 2017, doi: 10.1109/TCOMM.2016.2597282.
- [5] L. Dai, B. Wang, Y. Yuan, S. Han, C. L. I, and Z. Wang, “Non-orthogonal multiple access for 5G: Solutions, challenges, opportunities, and future research trends,” *IEEE Commun. Mag.*, vol. 53, no. 9, pp. 74–81, 2015, doi: 10.1109/MCOM.2015.7263349.
- [6] S. M. R. Islam, N. Avazov, O. A. Dobre, and K. S. Kwak, “Power-Domain Non-Orthogonal Multiple Access (NOMA) in 5G Systems: Potentials and Challenges,” *IEEE Commun. Surv. Tutorials*, vol. 19, no. 2, pp. 721–742, 2017, doi: 10.1109/COMST.2016.2621116.
- [7] Y. Chen *et al.*, “SCMA: A promising non-orthogonal multiple access technology for 5G networks,” *IEEE Veh. Technol. Conf.*, vol. 0, 2016, doi: 10.1109/VTCFall.2016.7881213.
- [8] A. Sultana, I. Woungang, A. Anpalagan, L. Zhao, and L. Ferdouse, “Efficient Resource Allocation in SCMA-Enabled Device-to-Device Communication for 5G Networks,” *IEEE Trans. Veh. Technol.*, vol. 69, no. 5, pp. 5343–5354, 2020, doi: 10.1109/TVT.2020.2983569.
- [9] D. Zhai, M. Sheng, X. Wang, Z. Sun, C. Xu, and J. Li, “Energy-Saving Resource Management for D2D and Cellular Coexisting Networks Enhanced by Hybrid Multiple Access Technologies,” *IEEE Trans. Wirel. Commun.*, vol. 16, no. 4, pp. 2678–2692, 2017, doi: 10.1109/TWC.2017.2671863.

- [10] K. Zhao *et al.*, “Resource allocation in device-to-device communication underlaid cellular network using SCMA: An opportunistic approach,” *2015 IEEE/CIC Int. Conf. Commun. China, ICCC 2015*, 2016, doi: 10.1109/ICCChina.2015.7448748.
- [11] D. Zhai, “Adaptive codebook design and assignment for energy saving in SCMA networks,” *IEEE Access*, vol. 5, pp. 23550–23562, 2017, doi: 10.1109/ACCESS.2017.2764120.
- [12] Y. O. Imam-Fulani *et al.*, “5G Frequency Standardization, Technologies, Channel Models, and Network Deployment: Advances, Challenges, and Future Directions,” *Sustain.*, vol. 15, no. 6, 2023, doi: 10.3390/su15065173.
- [13] X. Chen, D. W. K. Ng, W. Yu, E. G. Larsson, N. Al-Dahir, and R. , “Massive Access for 5G and beyond,” *IEEE J. Sel. Areas Commun.*, vol. 39, no. 3, pp. 615–637, 2021, doi: 10.1109/JSAC.2020.3019724.
- [14] B. Zhao, J. Liu, B. Mao, and S. Li, “Optimal Resource Allocation for Random Multiple Access Oriented SCMA-V2X Networks,” *IEEE Trans. Veh. Technol.*, vol. 72, no. 8, pp. 10921–10932, 2023, doi: 10.1109/TVT.2023.3262274.
- [15] M. S. M. Gismalla *et al.*, “Survey on Device to Device (D2D) Communication for 5GB/6G Networks: Concept, Applications, Challenges, and Future Directions,” *IEEE Access*, vol. 10, no. Vlc, pp. 30792–30821, 2022, doi: 10.1109/ACCESS.2022.3160215.
- [16] B. S. Khan, S. Jangsher, A. Ahmed, and A. Al-Dweik, “URLLC and eMBB in 5G Industrial IoT: A Survey,” *IEEE Open J. Commun. Soc.*, vol. 3, no. July, pp. 1134–1163, 2022, doi: 10.1109/OJCOMS.2022.3189013.
- [17] V. S. W. W. Prabowo, L. Meylani, E. R. A. Majid, and A. A. Muayyadi, “Power control using particle swarm optimization method in resource allocation process on D2D underlaying communication,” *J. Infotel*, vol. 14, no. 3, pp. 220–226, 2022, doi: 10.20895/infotel.v14i3.759.
- [18] ITU-R, “M2410 - Minimum requirements related to technical performance for IMT-2020 radio interface(s),” *Work. Party 5D*, vol. November, no. Report ITU-R M.2410-0, pp. 1–11, 2017, [Online]. Available: [https://www.itu.int/dms\\_pub/itu-r/opb/rep/R-REP-M.2410-2017-PDF-E.pdf](https://www.itu.int/dms_pub/itu-r/opb/rep/R-REP-M.2410-2017-PDF-E.pdf)
- [19] O. Kanhere, H. Poddar, Y. Xing, D. Shakya, S. Ju, and T. S. Rappaport, “A Power Efficiency Metric for Comparing Energy Consumption in Future Wireless Networks in

- the Millimeter-Wave and Terahertz Bands,” *IEEE Wirel. Commun.*, vol. 29, no. 6, pp. 56–63, 2022, doi: 10.1109/MWC.005.2200083.
- [20] Z. Bai, M. Li, Y. Dong, H. Zhang, and P. Ma, “Joint Fair Resource Allocation of D2D Communication Underlaying Downlink Cellular System With Imperfect CSI,” *IEEE Access*, vol. 6, pp. 63131–63142, 2018, doi: 10.1109/ACCESS.2018.2873364.
  - [21] Y. Ida and T. Matsumoto, “Interleaved block allocation and power combination for frequency symbol spreading multiuser diversity OFDMA,” *Eurasip J. Wirel. Commun. Netw.*, vol. 2022, no. 1, 2022, doi: 10.1186/s13638-022-02131-5.
  - [22] M. Rebhi, K. Hassan, K. Raoof, and P. Charge, “Sparse Code Multiple Access: Potentials and Challenges,” *IEEE Open J. Commun. Soc.*, vol. 2, no. June, pp. 1205–1238, 2021, doi: 10.1109/OJCOMS.2021.3081166.
  - [23] H. Nikopour and H. Baligh, “Sparse code multiple access,” *IEEE Int. Symp. Pers. Indoor Mob. Radio Commun. PIMRC*, pp. 332–336, 2013, doi: 10.1109/PIMRC.2013.6666156.
  - [24] R. V. Akhpashev and A. V. Andreev, “COST 231 Hata adaptation model for urban conditions in LTE networks,” *Int. Conf. Young Spec. Micro/Nanotechnologies Electron Devices, EDM*, vol. 2016-Augus, pp. 64–66, 2016, doi: 10.1109/EDM.2016.7538693.
  - [25] T. Specification, G. Radio, A. Network, and R. Aspects, “3gpp tr 36.843,” vol. 1, no. Release 12, pp. 1–50, 2014.
  - [26] F. Kahyangan *et al.*, “Resource block allocation : performance comparison of auction , greedy , and round robin algorithms,” vol. 3, no. 2, pp. 20–32, 2024.
  - [27] F. T. Elektro, T. Univeristy, F. T. Elektro, T. Univeristy, F. T. Elektro, and T. Univeristy, “Algoritma Alokasi Sumber Daya Radio pada Sistem Komunikasi Nirkabel menggunakan Genetika dan Metode Clustering,” vol. 11, no. 6, pp. 5669–5675, 2024.
  - [28] V. S. W. Prabowo, B. Pamukti, A. Fahmi, N. M. Adriansyah, and N. Andini, “Joint-greedy allocation algorithm on D2D communication underlaying networks,” *Proc. - 2019 IEEE Asia Pacific Conf. Wirel. Mobile, APWiMob 2019*, no. February 2022, pp. 48–52, 2019, doi: 10.1109/APWiMob48441.2019.8964175.
  - [29] P. S. Nima, P. S. Swapna, and S. S. Pillai, “Cluster based OFDMA Resource Allocation in Femtocell Networks,” vol. 11, no. 5, pp. 10–16, 2016, doi: 10.9790/2834-1105031016.

- [30] M. Shafi *et al.*, “5G: A tutorial overview of standards, trials, challenges, deployment, and practice,” *IEEE J. Sel. Areas Commun.*, vol. 35, no. 6, pp. 1201–1221, 2017, doi: 10.1109/JSAC.2017.2692307.
- [31] M. Erza, F. Putrafasa, A. Fahmi, V. Sigit, and W. Prabowo, “Analisis Penggunaan Algoritma Berbasis Heuristik Untuk Alokasi Resource Block Pada Komunikasi D2D Analysis of Heuristic-Based Algorithms Utilization for Resource Block Allocation in D2D Communications,” *e-Proceeding Eng.*, vol. 7, no. 2, p. 3308, 2020.
- [32] A. Rozak, B. R. Ardiansyah, V. Sigit Widhi Prabowo, and N. Mufti Adriansyah, “Radio Resource Allocation Using Graph Algorithm for Device-To-Device Underlay Communication System,” *Commun. Syst.*, vol. 9, no. 2, pp. 8–13, 2022, doi: 10.25124/jmecs.v9i2.5719.
- [33] S. F. Fitria Rachmawati, V. S. Widhi Prabowo, L. Anggayani, and N. M. Adriansyah, “Performance Analysis of Radio Resource Allocation to Maximize Power Efficiency in Device-To-Device Communication,” *J. Meas. Electron. Commun. Syst.*, vol. 10, no. 1, p. 1, 2023, doi: 10.25124/jmecs.v10i1.5812.
- [34] A. Milleano, “Analisis Kinerja Alokasi Sumber Daya Pada Orientasi Kluster Untuk Komunikasi Device-To- Device,” vol. 8, no. 6, pp. 2622–2627, 2022.
- [35] C. King, “Fundamentals of wireless communications,” *2014 67th Annu. Conf. Prot. Relay Eng. CPRE 2014*, pp. 470–474, 2014, doi: 10.1109/CPRE.2014.6799022.
- [36] V. S. Widhi Prabowo, A. Fahmi, N. M. Adriansyah, and N. Andini, “Energy efficient resources allocations for wireless communication systems,” *Telkomnika (Telecommunication Comput. Electron. Control.)*, vol. 17, no. 4, pp. 1625–1634, 2019, doi: 10.12928/TELKOMNIKA.V17I4.10135.
- [37] I. G. Fraimis and S. A. Kotsopoulos, “QoS-based proportional fair allocation algorithm for OFDMA wireless cellular systems,” *IEEE Commun. Lett.*, vol. 15, no. 10, pp. 1091–1093, 2011, doi: 10.1109/LCOMM.2011.081211.111417.