

ABSTRACT

This final project single band microstrip antenna with array of triangle slot element (microstrip antenna is designed, implemented, and measurement using stacked multiresonator at frequency 2,4 GHz that operates at the range of 2400 MHz – 2483 MHz of frequency spectrum. So that bandwidth required at RF level is about 83 MHz. Stacked multiresonator method have been proven able to add bandwidth of antenna mikrostrip. One of way to add bandwidth of antenna mikrostrip is with using substrat which thick progressively and small dielectric constant. This microstrip antena design using a feeding method which called electromagnetically coupled (EMC). By using EMC, the undesirable radiation become smaller and also offers wideband characteristic without some network matching. Ansoft HFSS 9.2 was used as the simulator software at this final project.

The antenna which support W-LAN (Wireless-Local Area Network) that defined the range of 2300 MHz – 2520 MHz frequency spectrum is designed. This antenna also good operates for WiMAX (*Worldwide Interoperability for Microwave Access*) aplication at the range of 2300 MHz – 2390 MHz of frequency spectrum. Meanwhile the BWA (*Broadband Wireless Access*) operates at the range of 2500 MHz – 2520 MHz of frequency spectrum.

Prototype are made according to the model of simulation and the result which is obtained from the frequency measurement at $VSWR \leq 1,5$, that is at the range of 2400 MHz – 2483 MHz frequency spectrum. Meanwhile at $VSWR \leq 2$, obtained very wide of *bandwidth* that is 504 MHz at the range 2.178 MHz – 2.682 MHz frequency spectrum. The radiation pattern of the antenna is unidirectional and also its polarization is elliptical polarized. The available Gain of this antenna are able reach untill 5,864 dBi.

Kata kunci : Antena Mikrostrip, W-LAN, WIMAX, BWA, *stacked multiresonator, electromagnetically coupled (EMC).*